

450101-02708

**TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known see 37 C.F.R. 1.5)

**09/831694**INTERNATIONAL APPLICATION NO.  
**PCT/JP00/06198**INTERNATIONAL FILING DATE  
**11 SEPTEMBER 2000**PRIORITY DATE CLAIMED  
**14 SEPTEMBER 1999**TITLE OF INVENTION **IMAGE PRINTING SYSTEM**APPLICANT(S) FOR DO/EO/US **Yushi IHARA**

Applicants herewith submit to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)).
4. ☐ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☒ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☒ have not been made and will not be made.
8. ☐ A English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).



**Items 11 to 20 below concern document(s) or information included:**

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☒ Other items or information:

PCT/RO/101, PCT/ISA/210  
PCT/IB/301, 304, 308  
49 Sheets of Drawings, 1 Page Abstract**EXPRESS MAIL**Mailing Label Number: **EL742696095US**Date of Deposit: **May 10, 2001**

I hereby certify that this paper or fee is being deposited with the United States Postal Service

"Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents and Trademarks, Box PCT Washington, DC 20231.

  
(Typed or printed name of person mailing paper or fee)  
(Signature of person mailing paper or fee)

09/831694

21. ☒ The following fees are submitted

CALCULATIONS PTO USE ONLY

**BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5):**

Neither international preliminary examination fee (37 CFR 1.482)  
nor international search fee (37CFR 1.445(a)(2) paid to USPTO  
and International Search Report not prepared by the EPO or JPO .....\$1000.00

International preliminary examination fee (37 C.F.R. 1.482) not paid to  
USPTO but International Search Report prepared by the EPO or JPO .....\$860.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but  
international search fee (37 CFR 1.445(a)(2)) paid to USPTO .....\$710.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)  
but all claims did not satisfy provisions of PCT Article 33(1)-(4) .....\$690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)  
and all claims satisfied provisions of PCT Article 33(1)-(4) .....\$100.00

**ENTER APPROPRIATE BASIC FEE AMOUNT =****\$ 860.00**

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30  
months from the earliest claimed priority date (37 CFR 1.492(e)).

\$

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	
Total Claims	10 - 20 =	0	x \$18.00	\$ 0.00
Independent Claims	10 - 3 =	7	x \$80.00	\$ 560.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$270.00	\$
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$
<input type="checkbox"/> Applicant claims small entity status. See 37 C.F.R. 1.27. The fees indicated above are reduced by 1/2.				\$
<b>SUBTOTAL =</b>				\$
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$
<b>TOTAL NATIONAL FEE =</b>				\$ 1,420.00
Fee for recording the enclosed assignments (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). <b>\$40.00</b> per property				\$
<b>TOTAL FEES ENCLOSED =</b>				\$ 1,420.00
				Amount to be refunded:
				\$
				Charged:
				\$

a. ☒ One check in the amount of **\$ 1,420.00** to cover the above fees are enclosed.

b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \$ \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any  
overpayment to Deposit Account No. **50-0320**. A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit  
card information should not be included on this form.** Provide credit card information and authorization  
on PTO-2038.

**NOTE:** Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR  
1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

**WILLIAM S. FROMMER, ESQ.**  
**FROMMER LAWRENCE & HAUG LLP**  
**745 FIFTH AVENUE**  
**NEW YORK, NEW YORK 10151**

Dated: May 10, 2001

SIGNATURE

WILLIAM S. FROMMER

NAME

25,506

REGISTRATION NUMBER

49/PRTS

1

## DESCRIPTION

Image Printing System

## Technical Field

This invention relates to an image processing device and method, a printing device and method, an image printing system and method, and a recording medium having image processing and printing programs stored therein which are suitable for the use in a system for printing an image by using a printer device connected through an interface conformable to the IEEE (the Institute of Electrical and Electronics Engineers) 1394 standard.

## Background Art

The IEEE 1394 standard defines the physical and electrical standard for connectors provided in various equipments which are interconnected. As the equipments having such interfaces conformable to the IEEE 1394 standard are physically connected, hot plug and play for automatically carrying out high-speed transmission/reception of digital data and connection setting between the equipments can be realized. The IEEE 1394 standard has become popular as the serial interface standard standardized in the industry.

The IEEE 1394 interface has also become popular as the interface for connecting AV equipments, as well as in the computer field. Specifically, in the case

09831694-071901

where an STB (set top box) for receiving satellite broadcast and displaying it on a television unit and a printer device for printing an image are connected with each other through the IEEE 1394 interface, the STB controls the printer device by using the FCP (function control protocol) and AV/C protocol. In this case, the STB and the printer device have the FCP and AV/C protocol mounted thereon and operate in accordance with the FCP command and AV/C command.

In an image printing system having a printer device which is connected through the conventional IEEE 1394 interface and has the FCP and AV/C protocol mounted thereon and a controller for controlling the printer device, when printing a static image, setting items defined by the operation mode (operation\_mode\_parameters) indicating information for carrying out print setting are designated by the controller and stored into an asynchronous packet, and printing is carried out by the printer device. In this case, the controller carries out print setting in accordance with a request from the user. Such print setting is proposed in "1394 TRADE ASSOCIATION TA Document XXXXXXXX AV/C Printer Subunit Specification Version 1.0 Draft 0.5: 145."

Specifically, when printing by the printer device is controlled by the controller, the user sets information for setting the relation of an image and a print sheet in three stages of large, medium and small sizes (sizing), information for setting the printing direction of the print sheet (orientations), information for setting the printing position of the image (posx, posy), information indicating what number of times the same image should be printed within the print sheet (multiple\_tiled), information indicating

how many images should be printed on one page (number\_of\_pics), and information indicating how many copies should be printed (number\_of\_copies). The user stores these pieces of information into an asynchronous packet and transmits it to the printer device so as to carry out printing.

Meanwhile, in such controller and printer device, for example, if the information indicating how many images should be printed on one page is set so as to print four images on one page, four images contracted to 1/4 are allocated to the respective areas generated by quadrisecting one sheet, as shown in Fig.1.

However, in such controller and printer device, in the case of printing a plurality of images on one page, printing cannot be made in such a manner that a blank area is partly provided. For example, in the case of printing four images on one page, it is not possible to provide a blank area for one image and allocate three images contracted to 1/4 in the respective areas, as shown in Fig.2.

The present Applicant proposed the contents of the Japanese Patent Application No.H11-261279, which is the base of priority of the present application, to the IEEE 1394 Trade Association for standardization at suitable timing, and the contents of the proposal are made public as the following drafts by the IEEE 1394 Trade Association:

AV/C Printer Subunit Specification Version 1.0, Draft 0.97: 60 (2Q00 AVWG Off-Cycle Meeting on May 24-25, 2000); and

AV/C Printer Subunit Specification Version 1.0, Draft 0.7: 5 (1Q00 TA QM AV-WG on January 18, 2000).

## Disclosure of the Invention

Thus, in view of the foregoing status of the art, it is an object of the present invention to provide a print processing device and method which enables provision of a blank area in a part of one page in the case of printing a plurality of images on one page by an equipment connected through an interface conformable to the IEEE 1394 standard.

It is another object of the present invention to provide a printing device and method which enables provision of a blank area in a part of one page in the case of printing a plurality of images on one page by an equipment connected through an interface conformable to the IEEE 1394 standard.

It is another object of the present invention to provide an image printing system and method which enables provision of a blank area in a part of one page in the case of printing a plurality of images on one page by an equipment connected through an interface conformable to the IEEE 1394 standard.

It is still another object of the present invention to provide a recording medium having an image processing program and a printing program stored therein which enables provision of a blank area in a part of one page in the case of printing a plurality of images on one page by an equipment connected through an interface conformable to the IEEE 1394 standard.

An image processing device according to the present invention comprises: image processing means for performing image processing on an image signal inputted

from outside and thus generating image data; control information generation means for generating print control information including information indicating the number of print images on one page of a print sheet; and output means for including the image data generated by the image processing means and the print control information generated by the control information generation means into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device; the control information generation means generating print control information including information which includes a blank image in the image to be printed on the print sheet.

An image processing method according to the present invention comprises the steps of: performing image processing on an image signal inputted from outside and thus generating image data; generating print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank area in the image to be printed on the print sheet; and including the generated image data and the print control information into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device.

An image processing method according to the present invention comprises the steps of: performing image processing on an image signal inputted from outside and thus generating image data; generating a command instructing start of a print job with respect to the generated image data, a command including information indicating the number of print images on one page of a print sheet, and a capture command including print control information with respect to the generated image data; including the

generated image data and the respective commands into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device; and in the case where a blank image is included in an image area to be printed on the print sheet, setting the data quantity of image data and the number of pixels in an X-direction and a Y-direction at zero as print control information with respect to the blank image and setting the capture command at a value indicating that the image type of the image data is not considered.

A printing device according to the present invention comprises: input means to which image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet are inputted; and printing means for printing an image represented by the image data inputted to the input means in accordance with the print control information; the printing means setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image is inputted.

A printing method according to the present invention comprises the steps of: receiving input of image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet; printing an image



represented by the inputted image data in accordance with the print control information; and setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image in the image to be printed on the print sheet is inputted.

A printing method according to the present invention comprises the steps of: performing image processing on an image signal inputted from outside and thus generating image data; receiving input of the image data included in a packet conformable to the IEEE 1394 standard, a command instructing start of a print job with respect to the image data, a command including information indicating the number of print images on one page of a print sheet, and a capture command including print control information with respect to the generated image data; and setting an image area to be printed on the print sheet as a blank area in the case where the capture command is inputted which sets the data quantity of image data and the number of pixels in an X-direction and a Y-direction at zero as print control information and which is set at a value indicating that the image type of the image data is not considered

An image printing system according to the present invention comprises: a print processing device including image processing means for performing image processing on an image signal inputted from outside and thus generating image data, control information generation means for generating print control information including information indicating the number of print images on one page of a print sheet, and

output means for including the image data generated by the image processing means and the print control information generated by the control information generation means into a packet conformable to the IEEE 1394 standard and outputting the packet, the control information generation means generating print control information including information which includes a blank image in the image to be printed on the print sheet; and a printing device including input means to which image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet are inputted, and printing means for printing an image represented by the image data inputted to the input means in accordance with the print control information, the printing means setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image is inputted.

An image printing method according to the present invention comprises the steps of: performing image processing on an image signal inputted from outside and thus generating image data; generating print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet; including the generated image data and the print control information into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device;

receiving the image data included in a packet conformable to the IEEE 1394 standard and the print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet; printing an image represented by the received image data in accordance with the print control information; and setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image in the image to be printed on the print sheet is inputted.

A recording medium according to the present invention has an image processing program stored therein, the image processing program comprising the steps of: performing image processing on an image signal inputted from outside and thus generating image data; generating print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet; and including the generated image data and the print control information into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device.

A recording medium according to the present invention has a printing program stored therein, the printing program comprising the steps of: receiving input of image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to

be printed on the print sheet; printing an image represented by the inputted image data in accordance with the print control information; and setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image in the image to be printed on the print sheet is inputted.

#### Brief Description of the Drawings

Fig.1 illustrates an example of print in which four images contracted to 1/4 are allocated to the respective areas generated by quadrisecting one sheet.

Fig.2 illustrates an example of print in which a blank area can be produced in the case where four images are allocated on one print sheet.

Fig.3 shows an image printing system to which the present invention is applied.

Fig.4 is a block diagram showing the structure of an STB and a printer device constituting the image printing system to which the present invention is applied.

Fig.5 shows the data structure of an asynchronous packet transmitted/received between the STB and the printer device.

Fig.6 shows the data structure of a data part of the asynchronous packet.

Fig.7 is a time chart in transmitting the asynchronous packet from a data conversion section to a data input section.

Fig.8 illustrates the image type of a static image.

Fig.9 shows the data structure of an asynchronous packet including a capture

command.

Fig.10 illustrates the name of image type stored in "image\_format\_specifier".

Fig.11 illustrates another example of image type stored in "image\_format\_specifier".

Fig.12 illustrates the transmission order of pixel data in point-sequential transmission of static image data with a pixel format of YCC 4:2:2 to the printer device.

Fig.13 illustrates the transmission order of pixel data in point-sequential transmission of static image data with a pixel format of YCC 4:2:0 to the printer device.

Fig.14 illustrates the transmission order of pixel data in line-sequential transmission of static image data with a pixel format of YCC 4:2:2 to the printer device.

Fig.15 illustrates the transmission order of pixel data in line-sequential transmission of static image data with a pixel format of YCC 4:2:0 to the printer device.

Fig.16 illustrates point-sequential transmission of a static image of an image type 480\_422\_4x3.

Fig.17 illustrates point-sequential transmission of a static image of an image type 480\_420\_4x3.

Fig.18 illustrates line-sequential transmission of the static image of the image

type 480\_422\_4×3.

Fig.19 illustrates plane-sequential transmission of the static image of the image type 480\_420\_4×3.

Fig.20 shows the data structure of an asynchronous packet including an operation mode 2 command.

Fig.21 illustrates the contents of “subfunction” included in the operation mode 2 command.

Fig.22 illustrates the contents of “Operation\_mode2\_parameters” included in the operation mode 2 command.

Fig.23 illustrates the contents of “media\_type” included in “Operation\_mode2\_parameters”.

Fig.24 illustrates the meaning of each setting item included in “media\_type”.

Fig.25 illustrates the contents of “media\_size” included in “Operation\_mode2\_parameters”.

Fig.26 illustrates the meaning of each setting item included in “media\_size”.

Fig.27 illustrates another example of contents of “media\_size” included in “Operation\_mode2\_parameters”.

Fig.28 illustrates the meaning of another example of the meaning of each setting item included “media\_size”.

Fig.29 illustrates the meaning of still another example of the meaning of each setting item included “media\_size”.

Fig.30 illustrates the contents of “print\_quality” included in “Operation\_mode2\_parameters”.

Fig.31 illustrates the meaning of each setting item included in “print\_quality”.

Fig.32 illustrates the contents of “mono\_color” included in “Operation\_mode2\_parameters”.

Fig.33 illustrates the meaning of each setting item included in “mono\_color”.

Fig.34 illustrates another example of the contents of “mono\_color” included in “Operation\_mode2\_parameters”.

Fig.35 illustrates another example of the meaning of each setting item included in “mono\_color”.

Fig.36 illustrates the contents of “offset” included in “Operation\_mode2\_parameters”.

Fig.37 illustrates the meaning of each setting item included in “offset”.

Fig.38 illustrates the contents of “layout\_type” included in “Operation\_mode2\_parameters”.

Fig.39 illustrates the meaning of “layout\_type”.

Fig.40 illustrates another example of the command packet including the operation mode command.

Fig.41 illustrates the meaning of each setting item included in the command packet including the operation mode command.

Fig.42 is a flowchart for explaining the processing procedure of print processing

carried out by the printer device constituting the image printing system to which the present invention is applied.

Fig.43 is a flowchart for explaining the processing procedure of a CPU of the STB when an image displayed on a television unit is to be printed by the printer device.

Fig.44 illustrates the processing for transmitting/receiving an asynchronous packet between the STB and the printer device and printing static image data by the printer device.

Fig.45 illustrates an example of print in the case where four images are allocated on one print sheet by the image printing system to which the present invention is applied.

Fig.46 illustrates an example of print in which a blank area cannot be produced in the case where four images are allocated on one print sheet.

Fig.47 illustrates an example of print in which a blank area can be produced in the case where four images are allocated on one print sheet.

Fig.48 illustrates the contents of a capture command transmitted to the printer device for producing a blank area.

Fig.49 illustrates the contents of another capture command transmitted to the printer device for producing a blank area.

Fig.50 illustrate an image type set for producing a blank area.

Fig.51 illustrates information to be stored in "subfunction" of a capture



command which is set for producing a blank area.

### Best Mode for Carrying Out the Invention

Preferred embodiments of the present invention will now be described in detail with reference to the drawings.

An image printing system to which the present invention is applied is constituted, for example, as shown in Fig.3.

This image printing system 1 includes an antenna 2 for receiving a dynamic image broadcast through, for example, a communication satellite, an STB (set top box) 3 for performing predetermined signal processing on the received dynamic image data, a television unit 4 for displaying a dynamic image or a static image, and a printer device 5 for printing and outputting the image.

The antenna 2 receives an image signal indicating a dynamic image and outputs the image signal to the STB 3. The image signal received by the antenna 2 is generated by superimposing image signals of multiple channels, and the dynamic image data is compressed in accordance with, for example, the MPEG (Moving Picture Experts Group) system and encrypted in accordance with a predetermined encryption system.

As dynamic image data in accordance with the NTSC (National Television System Committee) system is inputted to the television unit 4 through the STB 3, the television unit 4 displays the dynamic image. Also, in the case where the television

unit 4 is an HDTV, it displays the dynamic image as the dynamic image data in conformity with the HD (high definition) standard is inputted. The television unit 4 has the display state controlled by the STB 3 and also displays a static image and character information or the like.

The STB 3 has a demodulation section 11 for performing demodulation processing on the image signal received by the antenna 2, a descrambling section 12 for performing decryption processing on the dynamic image data, a data conversion section 13 for performing data conversion processing in conformity with the IEEE 1394 standard, a demultiplexer section 14 for carrying out processing to extract the dynamic image data in a predetermined channel, an image memory 15, an MPEG processing section 16 for carrying out decoding processing, a decoding memory 17, an NTSC encoding section 18 for converting the data to data to be displayed on the screen of the television unit 4, a display control section 19, a display memory 20, an operation input section 21 to which an instruction from the user is inputted, a RAM (random access memory) 22, and a CPU (central processing unit) 23 for controlling each section, as shown in Fig.4.

In the STB 3, the demodulation section 11, the descrambling section 12, the data conversion section 13, the demultiplexer section 14, the MPEG processing section 16, the operation input section 21, the RAM 22 and the CPU 23 are connected to a bus and the processing operation of the respective sections is controlled by the CPU 23 via the bus.

To the demodulation section 11, for example, an analog image signal indicating a dynamic image stream is inputted from the antenna 2. The demodulation section 11 performing demodulation processing and A/D conversion processing on the image signal from the antenna 2 and outputs the resultant digital dynamic image data to the descrambling section 12. Also, a control signal from the CPU 23 is inputted to the demodulation section 11 via the bus, and the demodulation section 11 performing demodulation processing and A/D conversion processing based on the control signal.

The descrambling section 12 carries out decryption processing with respect to the dynamic image data from the demodulation section 11. Specifically, the encrypted dynamic image data is inputted to the descrambling section 12, and the descrambling section 12 carries out decryption processing in accordance with the encryption system of the inputted dynamic image data. Then, the descrambling section 12 outputs the decrypted dynamic image data to the data conversion section 13. A control signal from the CPU 23 is inputted to the descrambling section 12 via the bus, and the descrambling section 12 carried out decryption processing using the encryption key information included in the control signal.

The data conversion section 13 is constituted, for example, by an interface circuit conformable to the IEEE 1394 standard. The data conversion section 13 performs signal processing in conformity with the IEEE 1394 standard with respect to the dynamic image data from the descrambling section 12 in response to the control signal from the CPU 23, thereby carrying out processing to include the inputted

dynamic image data or static image data into a packet conformable to the IEEE 1394 standard. In this case, the data conversion section 13 carries out processing to generate an isochronous packet when transmitting temporally continuous data such as dynamic image data, or to generate an asynchronous packet 100 as shown in Fig.5 when transmitting static data such as static image data, a command, or data for connection setting.

The asynchronous packet 100 shown in Fig.5 has a header portion 101 conformable to the IEEE 1394 standard, and a data portion 102.

In the header portion 101, the ID of the packet receiving side, that is, destination ID indicating the ID of the printer device 5 (destination\_ID), transaction label (tl), retry code (rt), priority (pri), ID of the packet transmitting side, that is, source ID indicating the ID of the STB 3 (source\_ID), destination\_offset indicating the memory address of the packet receiving side, data field length (data\_length), extended transaction code (extended\_tcode), and CRC of the header field indicating CRC with respect to the header portion 101 (header\_CRC) are stored.

In the data portion 102, the data field containing the data conformable to the FCP (Function Control Protocol) and AV/C protocol, and data CRC indicating CRC with respect to the data portion 102 (data\_CRC) are stored.

In the data field, as the information conformable to the FCP, the CTS (Command Transaction set), command type, subunit type indicating the type of the subunit of the packet receiving side (subunit\_type), and subunit ID indicating the ID

of the subunit of the packet receiving side (subunit\_ID) are stored, as shown in Fig.6. The subunit of the packet receiving side corresponds to the data input section 31 of the printer device 5, and type of the subunit of the packet receiving side is expressed by “00010” in the case of the printer device 5.

In the data field, the static image data to be transmitted to the printer device 5 (data) and the AV/C command with respect to the printer device 5 (command) are stored subsequent to the subunit ID. The command stored in the data field is a command included in the command set referred to as the AV/C command for controlling the printer device 5. When the type of the FCP is classified and the packet to be transmitted is a command, if its value is 0000, the AV/C command defined by the AV/C digital interface command set of IEEE 1394 is stored in the data field of the data portion 102 as the CTS.

When outputting the isochronous packet to the outside, the data conversion section 13 transmits the isochronous packet at a regular interval.

When transmitting the asynchronous packet 100 including static image data to be printed by the printer device 5, the data conversion section 13 transmits the asynchronous packet 100 in a cycle of 125 microseconds, as shown in Fig.7. In this case, the data conversion section 13 first transmits a cycle start packet 111 as the asynchronous packet 100 in which cycle time data (cycle\_time\_data) indicating the cycle start (Cycle\_start) is included in the header portion 101, and then transmits a command packet 112 in which a capture command indicating that static image data is

to be sent at a gap of a predetermined time period is included in the data portion 102. Then, the data conversion section 13 transmits in each cycle a data packet 113 in which the static image data is stored in the data portion 102, to the printer device 5 which received the capture command.

When outputting the static image data to the printer device 5, the data conversion section 13 follows the asynchronous arbitration. That is, when outputting the static image data to the printer device 5, the data conversion section 13 outputs each asynchronous packet 100 including the static image data in accordance with the response from the printer device 5.

Specifically, the data conversion section 13 carries out processing in the transaction layer, link layer and physical layer, with the serial bus managed in conformity with the IEEE 1394 standard. Thus, the data conversion section 13 sets the connection relation with the printer device 5 in accordance with the control from the CPU 23, then generates the asynchronous packet 100 including the static image data and the overhead as control information, and transmits in each cycle the asynchronous packet 100 to the printer device 5 connected in conformity with the IEEE 1394 standard, thus carrying out time-sharing control.

On the other hand, when the dynamic image data received by the STB 3 is to be displayed as it is on the television unit 4 without carrying out processing in conformity with the IEEE 1394 standard, the data conversion section 13 outputs the dynamic image data from the descrambling section 12 to the demultiplexer section 14

on the basis of the control signal from the CPU 23.

The demultiplexer 14 carries out channel selection processing to select the channel designated by the CPU 23 from the plural channels superimposed on the dynamic image data from the data conversion section 13, and outputs only the dynamic image data representing the designated channel to the MPEG processing section 16.

To the demultiplexer section 14, the static image data including luminance information and color-difference information is inputted from the MPEG processing section 16 under the control of the CPU 23. The demultiplexer section 14 stores the static image data to the image memory 15 and outputs the static image data to the data conversion section 13 in accordance with the control from the CPU 23.

The MPEG processing section 16 carries out decoding processing in conformity with the MPEG standard with respect to the dynamic image data from the demultiplexer section 14 on the basis of the control signal from the CPU 23, thereby outputting non-compressed dynamic image data to the NTSC processing section 18. Thus, the MPEG processing section 16 forms each frame constituting the dynamic image as an image (hereinafter referred to as YCC image) consisting of pixel data including the luminance information (Y) and the color-difference information (Cr, Cb). In this case, the MPEG processing section 16 uses as the work area the dynamic image data of plural frames, which is the decoding processing target, while sequentially storing the dynamic image data to the MPEG memory 17.

The MPEG processing section 16 generates a YCC image of a pixel format such

that the sampling frequency ratio of the luminance information Y, color-difference information Cr and color-difference information Cb is 4:2:2, that is, a pixel format produced by vertically or horizontally halving the color-difference information Cr, Cb with respect to the luminance information Y. Also, the MPEG processing section 16 vertically and horizontally halves the color-difference information Cr, Cb with respect to the luminance information Y, and thus generates a YCC image of a pixel format such that the sampling frequency ratio of the luminance information Y, color-difference information Cr and color-difference information Cb is 4:2:0. In the pixel format of 4:2:0, though odd lines have the sampling frequency ratio of 4:2:0 without including the color-difference information Cb while even lines have the sampling frequency ratio of 4:0:2 without including the color-difference information Cr, the ratio of 4:2:0 is used as a representative ratio. The MPEG processing section 16 may also generate a YCC image having a pixel format of 4:4:4 without reducing the color-difference information Cr, Cb as well as the image formats of 4:2:2: and 4:2:0.

The MPEG processing section 16 carries out encoding processing in conformity with the MPEG standard with respect to the dynamic image data from the NTSC processing section 18 on the basis of the control signal indicating the compression rate or the like from the CPU 23. Thus, the MPEG processing section compresses the dynamic image data in the direction of time base and in the spatial direction, and outputs the compressed dynamic image data to the demultiplexer section 14. In this case, the MPEG processing section 16 carries out processing to store the dynamic



image data of the plural frames as the encoding processing target to the MPEG memory 17.

The NTSC processing section 18 carries out encoding processing so that the dynamic image data inputted from the MPEG processing section 16 is processed to become dynamic image data of the NTSC system that can be displayed on the screen of the television unit 4, and then outputs the resultant dynamic image data to the television unit 4.

The display control section 19 carries out processing to display the dynamic image data of the NTSC system on the television unit 4 by the NTSC processing section 18. In this case, the display control section 19 sequentially stores the data as the processing target to the display memory 20.

Specifically, the display control section 19 carries out processing to control the image size of each frame constituting the dynamic image data when displayed on the television unit 4, to the size of 720 pixels  $\times$  480 pixels in the NTSC system or 1920 horizontal pixels  $\times$  1080 vertical pixels in the HD (high definition) system, in accordance with the television unit 4. In this case, when generating data of one pixel, the display control section 19 carries out processing to output data to the television unit 4 by using 16-bit information used in the pixel format such that the sampling frequency ratio of the luminance signal Y, color-difference signal Cr and color-difference signal Cb is 4:2:2 or information used in the pixel format such that the sampling frequency ratio of the luminance signal Y, color-difference signal Cr and

color-difference signal Cb is 4:2:0.

Moreover, not only in the case of outputting to the television unit 4 in accordance with the above-described system, the display control section 19 may also generate an image of an image type (Image Type) defining the size of the image (pixel\_x, pixel\_y), scanning direction (interlaced/progressive), pixel format (pixel format), aspect ratio of the screen (screen aspect ratio), aspect ratio of the pixel (pixel aspect ratio), and the data quantity (image size), as shown in Fig.8. In Fig.8, an image type having pixel\_y of 720 pixels, a pixel format of 4:2:2 and a screen aspect ratio of 16:9 is referred to as 720\_422\_16×9. The display control section 19 is also capable of generating static images of image types 720\_422\_16×9 and 720\_420\_16×9, which are image types of the digital television broadcasting system used in the United States. The display control section 19 is also capable of generating images of 576\_422\_4×3 and 522\_420\_4×3, which are image types in accordance with the PAL (phase alternation by line) system.

The operation input section 21 generates an operation input signal and outputs it to the CPU 23, as the user operates an operation button or the like provided on the STB 3. Specifically, the operation input section 21 generates an operation input signal to the effect that the dynamic image displayed on the television unit 4 by the user is to be temporarily stopped to print the static image by the printer device 5.

When generating the operation input signal to the effect that the static image is to be printed by the printer device 5, the operation input section 21 generates an

operation input signal designating the print sheet type setting, print sheet size setting, print quality setting, print color setting, position offset setting and layout setting in accordance with the print setting screen displayed on the television unit 4, and outputs the operation input signal to the CPU 23.

The CPU 23 generates a control signal for controlling the above-described respective sections constituting the STB 3, on the basis of the operation input signal from the operation input section 21.

When displaying the image signal received by the antenna 2, the CPU 23 outputs control signals to the demodulation section 11, the descrambling section 12, the data conversion section 13, the demultiplexer section 14 and the MPEG processing section 16, thus carrying out control so that demodulation, decryption processing, channel selection processing and decoding processing in conformity with the MPEG standard are carried out with respect to the dynamic image data.

The CPU 23 also generates a control signal so as to read into the image memory 15 the static image data of a frame unit stored in the display memory 20 at the time point when the operation input signal is inputted, of the dynamic image displayed on the television unit 4 in accordance with the operation input signal from the operation input section 21.

Moreover, when the operation input signal to the effect that print setting is to be carried out is inputted to the CPU 23 from the operation input section 21, the CPU 23 controls the display control section 19 to display the print setting screen on the

television unit 4 and carries out control so as to output the operation input signal in accordance with the above-described various print settings to the data conversion section 13.

When the operation input signal to the effect that an image having static image data generated is to be printed by the printer device 5 is inputted to the CPU 23, the CPU 23 controls the demultiplexer section 14 and the data conversion section 13, and thus carries out control so as to output a YCC image which is static image data of a frame unit stored in the image memory 15 and which includes luminance information Y and color-difference information Cr, Cb to the printer device 5 through the data conversion section 13, which is the interface circuit conformable to the IEEE 1394 standard.

In this case, when transmitting the static image data to the printer device 5 under the control of the CPU 23, the data conversion section 13 transmits the asynchronous packet 100 having stored therein a capture command as shown in Fig.9 subsequent to the subunit ID shown in Fig.6, and thus transmits the capture command for receiving the static image data to the printer device 5.

In the capture command shown in Fig.9, a capture (CAPTURE) command as opcode (operation code), expressed by a hexadecimal number  $XX_{16}$ , is stored. Subsequently, "subfunction" is stored as operand[0], and as operand[1], "source\_subunit\_type" is stored in upper five bits and "source\_subunit\_ID" is stored in lower three bits. As operand[2], "source\_plug" is stored. As operand[3], "status"

is stored. As operand[4], “dest\_plug” is stored. Subsequently, in the capture command, “print\_job\_ID” is stored as operand[5] to operand[16], “data\_size” is stored as operand[17] to operand[20], “image\_size\_x” is stored as operand[21] to operand[22], “image\_size\_y” is stored as operand[23] to operand[24], “image\_format\_specifier” is stored as operand[25], “reserved” is set as operand[27] to operand[29], “Next\_pic” is stored as operand[30], and “Next\_page” is stored as operand[31] to operand[32].

The above-mentioned “source\_subunit\_type” is the information indicating the type of the subunit for transmitting the asynchronous packet 100 from the side of the STB 3, and “source\_subunit\_ID” is the ID of the subunit for transmitting the asynchronous packet 100. “Source\_plug” is the plug number of the subunit for transmitting the asynchronous packet 100, and “dest\_plug” is the plug number of the subunit for receiving the asynchronous packet 100. “Print\_job\_ID” is the ID of processing (job) for printing one static image. “Data\_size” is the data quantity transmitted from the STB 3 to the printer device 5 when printing the static image by the printer device 5. “Image\_size\_x” is the number of pixels in the x-direction corresponding to the image type shown in Fig.8, and “image\_size\_y” is the number of pixels in the y-direction corresponding to the image type. “Image\_format\_specifier” is the name of the image type. “Reserved” is constituted by an arbitrary number of bits and is provided for setting the number of bits of the entire capture command to a multiple of 4. By providing this “reserved”, a suitable number of bits as a data unit

can be set when transmitting a packet conformable to the IEEE 1394 standard.

In “image\_format\_specifier”, the name of the image type discriminated by a hexadecimal value (Value) is stored, as shown in Fig.10. In Fig.10, “chunky” in the name of the image type indicates a static image transmitted point-sequentially from the data conversion section 13 to the printer device 5, and “liner” indicates a static image transmitted line-sequentially from the data conversion section 13 to the printer device 5.

In “image\_format\_specifier”, there may also be stored the name of the image type expressed by a hexadecimal value (Value, Sub-value) as shown in Fig.11 and not including the information related to the number of pixels unlike the image type shown in Fig.10, as well as the description of the name of the image type as shown in Fig.10. In this case, the number of pixels to be printed by the printer device 5 is defined by “image\_size\_x” described as operands[21] to [22] of the capture command shown in Fig.9 and “image\_size\_y” described as operands[23] to [24].

For example, when hexadecimal 00 (Meaning: sRGB raw) is described in msb of “image\_format\_specifier”, it is indicated that image data is transmitted as RGB data to the printer device 5. When hexadecimal 00 is described in msb of “image\_format\_specifier” and hexadecimal 00 (Type: sRGB raw) is described in lsb, RGB data is transmitted in the order of R, G, B, R, G, B, ... When 01 (Type: sRGB raw, quadlet) is described in lsb, RGB data is transmitted in the order of R, G, B, 0, R, G, B, 0, ... That is, when 00 is described in msb, 0-data is transmitted between B

and R and thus 4-byte data consisting of R, G, B, 0 as a unit is transmitted.

When hexadecimal 01 (Meaning: YCC raw) is described in msb of “image\_format\_specifier”, it is indicated that image data is transmitted as YCC data to the printer device 5. Moreover, when hexadecimal 01 is described in msb of “image\_format\_specifier” and hexadecimal 0X (X is a variable) (Type: YCC4:2:2:raw/pixel) is described in lsb, luminance information and color-difference information are point-sequentially (chunky) transmitted in the pixel format of 4:2:2, and when 1X (Type: YCC4:2:2:raw/line) is described in lsb, data of the pixel format of 4:2:2 is line-sequentially (liner) transmitted. When hexadecimal 8X (Type: YCC4:2:0raw/chunky) is described in lsb, luminance information and color-difference information are point-sequentially (chunky) transmitted in the pixel format of 4:2:0, and when 9X (Type: YCC4:2:0 raw/line) is described in lsb, data of the pixel format of 4:2:0 is line-sequentially (liner) transmitted.

Meanwhile, when hexadecimal 01 (Meaning: YCC raw) is described in msb of “image\_format\_specifier” and hexadecimal X0 to XC is described in lsb, designation of the pixel ratio (Pixel ratio 1.00×1.00, Pixel ratio 1.19×1.00, or Pixel ratio 0.89×1.00), designation of the color space (ITU-R (International telecommunications Union - Radiocommunication Sector) BT.709-2, ITU-R BT.601-4, or ITU-R BT.1203), and designation of point-sequential (chunky) or line-sequential (line) are carried out so as to transmit data. Moreover, when hexadecimal X0 to X4 is described in lsb, it is indicated that an interlaced image is transmitted, and when X8 to XC is

described in lsb, it is indicated that a progressive image is transmitted. Furthermore, when X0 to X2 and X8 to XA are described in lsb, it is indicated that data conformable to ITU-R BT.709-2 is transmitted. When X3 and XB are described, it is indicated that data conformable to ITU-R BT.601-4 is transmitted. When X4 and XC are described, it is indicated that data conformable to ITU-R BT.1203 (PAL system) is transmitted.

When hexadecimal 10 (Meaning: DCF Object) is described in msb of “image\_format\_specifier”, it is indicated that image data is transmitted in the format prescribed in the digital camera (DCF: Design rule for Camera Format) to the printer device 5. Moreover, when hexadecimal 10 is described in msb of “image\_format\_specifier” and hexadecimal 00 (Type: Exif2.1) is described as lsb, it is indicated that the image portion is transmitted in the Exif format such that a header having recorded therein the shooting status and conditions in the JPEG format is added. When hexadecimal 01 (Type: JFIF (JPEG File Interplay Format)) is described in lsb, it is indicated that image data of the JFIF format is transmitted. When 02 (Type: TIFF (Tag Image File Format)) is described in lsb, it is indicated that image data of the TIFF format is transmitted. When 0F (Type: JPEG (Joint Photographic Coding Experts Group)) is described, it is indicated that image data is transmitted in the JPEG format to the printer device 5.

Moreover, when hexadecimal 80 to 8F is described in msb of “image\_format\_specifier”, it is indicated that image data is transmitted in other formats, and data of the format designated by 00 to FF described in lsb is transmitted.



In “image\_format\_specifier”, apart from the above-described examples, hexadecimal FE (Meaning: Special meaning) in msb and 00 (Type: Unit Plug defined), 01 (Don’t care) in lsb can be provided.

After transmitting the asynchronous packet 100 having the capture command stored therein and receiving ACK (acknowledge) from the printer device 5, the data conversion section 13 transmits the asynchronous packet 100 including static image data to the printer device 5.

The transmission rules for static image data are as shown in Figs.12 to 15.

Fig.12 shows the transmission order of pixel data in point-sequential (chunky) transmission of static image data with a pixel format of YCC 4:2:2 to the printer device 5.

Fig.13 shows the transmission order of pixel data in point-sequential (chunky) transmission of static image data with a pixel format of YCC 4:2:0 to the printer device 4.

Fig.14 shows the transmission order of pixel data in line-sequential (liner) transmission of static image data with a pixel format of YCC 4:2:2 to the printer device 5.

Fig.15 shows the transmission order of pixel data in line-sequential (liner) transmission of static image data with a pixel format of YCC 4:2:0 to the printer device 5.

In Figs.12 to 15, Yi(Lj) indicates luminance information Y having a pixel

number  $i$  included in a line number  $j$ . The pixel number  $i$  used for designating the pixel of the luminance information  $Y$  has an integer value of 1 to  $N$ , and the line number  $j$  has an integer value of 1 to  $M$ .  $Cb_i(L_j)$  indicates color-difference information  $Cb$  having a pixel number  $i$  included in a line number  $j$ . The pixel number  $i$  used for designating the pixel of the color-difference information  $Cb$  has a value of 1, 3, 5, ...,  $N-1$ , and the line number  $j$  has an integer value of 1 to  $M$  in the case of YCC 4:2:2 or a value of 1, 3, 5, ...,  $N-1$  in the case of YCC 4:2:0.  $Cr_i(L_j)$  indicates color-difference information  $Cr$  having a pixel number  $i$  included in a line number  $j$ . The pixel number  $i$  used for designating the pixel of the color-difference information  $Cr$  has a value of 1, 3, 5, ...,  $N-1$ , and the line number  $j$  has an integer value of 1 to  $M$  in the case of YCC 4:2:2 or a value of 1, 3, 5, ...,  $N-1$  in the case of YCC 4:2:0.  $N$  indicates the total number of pixels in one line.  $M$  indicates the total number of lines within one screen.

In this case, when point-sequentially (chunky) transmitting to the printer device 5 the static image data included in the asynchronous packet 100 having an image type of 480\_422\_4x3 shown in Fig.10 and constituted by pixels with the pixels numbers 1 to 720 provided in the x-direction and the line numbers 1 to 480 provided in the y-direction, the data conversion section 13 transmits the pixel data as shown in Fig.16.

Specifically, subsequent to the address offset (`address_offset`), the data conversion section 13 transmits the luminance information  $Y1(L1)$ , luminance  $Y2(L1)$ , color-difference information  $Cb1(L1)$  and color-difference information  $Cr1(L1)$  with

respect to the pixel number 1 included in the line number 1. Then, subsequent to the pixel data up to the pixel number 720 included in the line number 1, the data conversion section 13 transmits the luminance information and color-difference information of the next line number 2 and subsequent line numbers. The data conversion section 13 transmits the pixel data up to the pixel number 720 included in the line number 480, thereby completing transmission of the static image data representing one static image.

When the image type is 480\_420\_4x3, the data conversion section 13 transmits the luminance information Y1(L1), luminance information Y2(L1), luminance information Y1(L2) and luminance information Y2(L2) with respect to the pixel number 1 included in the line number 1 subsequent to the address offset (address\_offset), and then transmits the color-difference information Cb1(L1), color-difference information Cr1(L1), luminance information Y3(L1) and luminance information Y4(L1) included in the pixel data of the pixel number 1, as shown in Fig.17. Then, the data conversion section 13 transmits the pixel data up to the pixel number 720 included in the line number 480, thereby completing transmission of the static image data representing one static image.

When line-sequentially transmitting the static image data having the image type of 480\_422\_4x3 included in the asynchronous packet 100, the data conversion section 13 transmits the luminance information Y1(L1), luminance information Y2(L1), luminance information Y3(L1), luminance information Y4(L1), ..., luminance

information  $Y720(L1)$  with respect to the line number 1 subsequent to the address offset (address\_offset), and then transmits the color-difference information  $Cb1(L1)$ , color-difference information  $Cr1(L1)$ , ..., color-difference information  $Cb720(L1)$  and color-difference information  $Cr720(L1)$  with respect to the line number 1, as shown in Fig.18. Then, the data conversion section 13 transmits the luminance information and color-difference information of the line number 2 and subsequent line numbers, and transmits the color-difference information  $Cr720(L480)$  of the line number 480, thereby completing transmission of the static image data.

When line-sequentially transmitting the static image data having the image type of 480\_420\_4x3 included in the asynchronous packet 100, the data conversion section 13 first transmits the luminance information  $Y1(L1)$  to luminance information  $Y720(L1)$  of the line number 1, the transmits the luminance information  $Y1(L2)$  to luminance information  $Y720(L2)$  of the line number 2, and then transmits the color-difference information  $Cb1(L1)$ , color-difference information  $Cr1(L1)$  to color-difference information  $Cb720(L1)$ , color-difference information  $Cr719(L1)$  of the line number 1, thus transmitting the pixel data of the line number 1 and the line number 2, as shown in Fig.19. Then, the data conversion section 13 transmits the luminance information and color-difference information of the line number 3 and subsequent line numbers, and transmits the color-difference information  $Cb719(L479)$  and color-difference information  $Cr719(L479)$ , thereby completing transmission of the static image data.

Moreover, when carrying out print setting by designating the print sheet type setting, print sheet size setting, print quality setting, print color setting, position offset setting and layout setting in accordance with the operation input signal from the operation input section 21, the data conversion section 13 stores into the command packet the operation mode 2 (OPERATION MODE2) parameters (hereinafter referred to as operation mode 2 parameter) included in the operation mode 2 command shown in Fig.20 which is different from “operation\_mode\_parameters” (hereinafter referred to as operation mode 1 parameter) already proposed by the IEEE 1394 standard.

The operation mode 1 parameters include information for setting the relation of an image and a print sheet in three stages of large, medium and small sizes (sizing), information for setting the printing direction of the print sheet (orientations), information for setting the printing position of the image (posx, posy), information indicating what number of times the same image should be printed within the print sheet (multiple\_tiled), information indicating how many images should be printed on one page (number\_of\_pics), and information indicating how many copies should be printed (number\_of\_copies).

In the operation mode 2 command shown in Fig.20, information indicating the operation mode 2 (OPERATION MODE2) command as opcode (operation code), expressed by hexadecimal “51”, is stored. Subsequently, “subfunction” is stored as operand[0], “status” is stored as operand[1], and “reserved” is stored as operand[2] to operand[4]. Then, “print\_job\_ID” is stored as operand[5] to operand[16], and

“Operation\_mode2\_parameters” (operation mode 2 parameters) indicating the specific contents of the print setting of the operation mode 2 command are stored as operand[17] to operand[31].

In “subfunction”, information expressed by hexadecimal 01 and referred as “get”, information expressed by hexadecimal 02 and referred to as “set”, or information expressed by hexadecimal 03 and referred to as “query” is stored, as shown in Fig.21.

The data conversion section 13 stores “get” in “subfunction” when obtaining the operation mode 2 parameters indicating the print setting information of the printer device 5, or stores “set” when setting the operation mode 2 parameters of the print device 5, or stores “query” when wishing to know the possible setting range of the operation mode 2 parameters of the print device 5. With respect to information expressed by other numbers than hexadecimal 01, 02 and 03, “reserved” is provided in “subfunction”.

When responding to the operation mode 2 command from the data conversion section 13, the data input section 31, which will be described later, generates an asynchronous packet in which the contents of “subfunction” are changed.

In “Operation\_mode2\_parameters”, print sheet type information (media\_type), print sheet size information (Media\_size), reserved area (reserved), print quality information (Print\_quality), print color information (Mono\_color), print offset position information (offset), and layout setting information (Layout\_type) are stored, as shown

in Fig.22.

In the print sheet type information (media\_type), one bit is allocated to each setting item and a plurality of setting items are sequentially arranged, as shown in Figs.23 and 24. Specifically, “device\_dependent”, “Plain\_paper” (normal paper), “Bond\_paper” (seal), “Special\_paper” (special paper), “Photo\_paper” (photographic paper), and “Transparency\_film” (OHP film) are sequentially arranged. The bit for each setting item is established by the data conversion section 13 or the data input section 31, thereby designating the type of the print sheet. In the print sheet type information, when the user does not specify the print sheet and the printer device 5 is caused to select the optimum print sheet type, the bit for “device\_dependent” is established.

In the print sheet size information (Media\_size), “device\_dependent”, “A5” (ISO and JIS A5), “A4” (ISO and JIS A4), “B5” (JIS B5), “Executive” (US Executive), “Letter” (US Letter), “Legal” (US Legal), “Reserved”, “Hagaki” (postcard), “Oufuku\_hagaki” (double postal card), “A6” (ISO and JIS A6 Card), “Index\_4×6” (US Index Card 4"×6"), “Index 5×8” (US Index Card 5"×8"), “A3” (ISO A3), “B4”, “Legal 11×17”, “Commercial10\_portrait” (US Commercial#10 (portrait)), “Commercial10\_landscape” (US Commercial#10 (landscape)), “DL” (International DL), “C6” (International C6), “A2” (US A2), and “Custom” (Custom paper) are stored, as shown in Fig.25 and 26. This print sheet size information designates the size of the print sheet as the bit for each setting item is established by the data conversion

section 13 or the data input section 31.

As another example of the print sheet size information (Media\_size), “device\_dependent” and “other” are stored, and the subsequently prescribed “letter” (North American letter size), “legal” (North American legal size), “na\_10×13\_envelope” (North American 10×13 envelope), “na\_9×12\_envelope” (North American 9×12 envelope), na\_number\_10\_envelope (North American 10 business envelope), “na\_7×9\_envelope” (North American 7×9), “na\_9×11\_envelope” (North American 9×11), “na\_10×14\_envelope” (North American 10×14 envelope), “na\_6×9\_envelope” (North American 6×9 envelope), “na\_10×15\_envelope” (North American 10×15 envelope), “a” (engineering A), “b” (engineering B), “c” (engineering C), “d” (engineering D), “iso a0” (ISO A0), “iso a1” (ISO A1), “iso a2” (ISO A2), “iso a3” (ISO A3), “iso a4” (ISO A4), “iso a5” (ISO A5), “iso a6” (ISO A6), “iso a7” (ISO A7), “iso a8” (ISO A8), “iso a9” (ISO A9), “iso a10” (ISO A10), “iso b0” (ISO B0), “iso b1” (ISO B1), “iso b2” (ISO B2), “iso b3” (ISO B3), “iso b4” (ISO B4), “iso b5” (ISO B5), “iso b6” (ISO B6), “iso b7” (ISO B7), “iso b8” (ISO B8), “iso b9” (ISO B9), “iso b10” (ISO B10), “iso c0” (ISO C0), “iso c1” (ISO C1), “iso c2” (ISO C2), “iso c3” (ISO C3), “iso c4” (ISO C4), “iso c5” (ISO C5), “iso c6” (ISO C6), “iso c7” (ISO C7), “iso c8” (ISO C8), “iso designated” (ISO Designated Long), “jis b0” (JIS B0), “jis b1” (JIS B1), “jis b2” (JIS B2), “jis b3” (JIS B3), “jis b4” (JIS B4), “jis b5” (JIS B5), “jis b6” (JIS B6), “jis b7” (JIS B7), “jis b8” (JIS B8), “jis b9” (JIS B9), “jis b10” (JIS B10), “index\_4×6” (North American Index Card 4"×6"), “index\_5×8” (North



American Index Card 5"×8"), "japanese\_hagaki" (Japanese Hagaki Postcard), and "japanese\_ouhuku\_hagaki" (Japanese Ouhuku-Hagaki Postcard) are sequentially stored, as shown in Figs.27, 28 and 29. The size of the print sheet is designated as the bit for each setting item is established by the data conversion section 13 or the data input section 31.

In the print quality information (Print\_quality), "device\_dependent", "economy" (speed first), "normal" (normal), and "best" (quality first) are stored, as shown in Figs.30 and 31. In this print quality information, the print quality is designated as the bit for each setting item is established by the data conversion section 13 or the data input section 31.

In the print color information (Mono\_color), "device\_dependent", "mono" (monochrome print), and "color" (color print) are stored, as shown in Figs.32 and 33. In this print color information, the print color is designated as the bit for each setting item is established by the data conversion section 13 or the data input section 31.

As another example of the print color information, "device\_dependent", "black\_white" (black-and-white print), "mono" (monochrome (gray scale) print), and "color" (color print) are stored, as shown in Figs.34 and 35.

In the print offset position information (offset), "Offset\_top" and "Offset\_left" are stored, as shown in Figs.36 and 37. "Offset\_top" and "Offset\_left" are expressed by hexadecimal numbers X000 to X999, and designate the offset position by 2 bytes using BCD (binary coded decimal). When X is hexadecimal 0, the print start position

in the inward direction (plus) of the print sheet is indicated. When X is 8, the print start position in the outward direction (minus) of the print sheet is indicated. Two of the lower three digits express the integer and the remaining one digit expresses the decimal place. Thus, the position of the origin at the upper left part of the print sheet is designated within a range of 00.0 to 99.9 mm from the top and left ends of the sheet, thus designating the print start position. When the print offset position information is expressed by hexadecimal FFFF, “device\_dependent” is indicated. When “subfunction” is “query” for inquiring the possible setting range of the operation mode 2 parameters, the possible maximum value is stored as the print offset position information.

In the layout setting information (Layout\_type), “Layout\_type” of 4 bytes is stored, as shown in Figs.38 and 39. This layout setting information indicates the type of layout as it is expressed by hexadecimal 00000000 to 0FFFFFFF. When it is expressed by FFFFFFFF, “device\_dependent” is indicated.

As another example of the command as shown in Fig.20, the data conversion section 13 may also output the above-described operation mode 1 and operation mode 2 as a single command to the printer device 5.

In this operation mode command, as shown in Fig.40, hexadecimal 41 in opcode expresses that the command is an operation command. Following “subfunction”, “status”, “next\_pic”, “next\_page” and “print\_job\_ID”, “operation\_mode\_parameters” corresponding to the above-described operation mode 1 parameters is stored in

operand[17] to operand[24], and “operation\_mode\_parameters” indicating print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information is stored in operand[25] to operand[29] corresponding to the operation mode 2 (OPERATION MODE2) parameters included in the operation mode 2 command of Fig.20. Such an operation command, in which the part of “operation\_mode\_parameters” is used for standard setting and the part of “operation\_mode\_optional\_parameters” is used for extended setting, is processed between the data conversion section 13 and the data input section 31.

In “operation\_mode\_parameters”, as described above, information of the same contents as those stored in the operation mode 1 command is stored.

In “operation\_mode\_optional\_parameters”, as shown in Fig.41, “media\_type” indicating the type of the print sheet for printing by the printer device 5, “media\_size” indicating the dimension of the print sheet for printing by the printer device 5, “print\_quality” indicating the print quality in printing by the printer device 5, and “mono\_color” are stored, similarly to “Operation\_mode2\_parameters” of Fig.22 stored in the operation mode 2 command of Fig.20, and “rendering\_intent” is further stored.

The printer device 5 has a data input section 31 for inputting static image data from the printer device 5, a ROM (read only memory) 32 in which a print control program is stored, a print engine 33 for carrying out printing on a print object, a RAM 34, and a CPU 35 for controlling each constituent portion, as shown in Fig.4.

The data input section 31 is constituted by an interface circuit conformable to the IEEE 1394 standard and carries out signal processing in conformity with the IEEE 1394 standard with respect to the static image data included in the asynchronous packet 100 from the STB 3 in accordance with a control signal from the CPU 35.

Specifically, the data input section 31 carries out processing in the transaction layer, link layer and physical layer, with the serial bus managed in conformity with the IEEE 1394 standard. Thus, the data input section 31 outputs the static image data included in the asynchronous packet 100 to the CPU 35.

When the command packet having the operation mode 2 parameters stored therein is received from the data conversion section 13, the data input section 31 carries out processing to output various print setting information to the CPU 35.

When it is discriminated that “get” for obtaining the operation mode 2 parameters indicating the print setting information of the printer device 5 is stored as “subfunction”, the data input section 31 recognizes the print setting to be obtained on the side of the STB 3, from the print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information. Then, the data input section 31 sends the packet including the operation mode 2 parameters with respect to the recognized print setting as the response to the data conversion section 13.

When it is discriminated that “set” for setting the operation mode 2 parameters of the printer device 5 is stored as “subfunction”, the data input section 31 recognizes

the print setting to be set on the side of the STB 3, from the print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information. Then, the data input section 31 outputs to the CPU 35 the information to the effect that the operation mode 2 parameters with respect to the recognized print setting should be set.

When it is discriminated that “query” for inquiring the possible setting range of the operation mode 2 parameters is stored as “subfunction”, the data input section 31 recognizes the print setting inquired by the data conversion section 13, by checking the bit for each setting item of the print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information. Then, the data input section 31 sends the asynchronous packet 100 including the possible setting value of the operation mode 2 parameters with respect to the print setting inquired by the data conversion section 13, as the response to the data conversion section 13.

Meanwhile, when the bit is established as “device\_dependent” in the print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information, the data input section 31 outputs the information to that effect to the CPU 35.

Moreover, when the data input section 31 is mechanically connected to the STB 3 through an optical cable or the like, the data input section 31 carries out connection setting with the data conversion section 13 of the STB 3 for transmission/reception of

the asynchronous packet 100 with the printer 5.

The print engine 33 is constituted by a print object holding/driving mechanism, a printer head, and a printer head driving mechanism. The print engine 33 is controlled by the CPU 35 and prints the static image to the print object.

The CPU 35 generates control signals for controlling the data input section 31 and the print engine 33. In this case, the CPU 35 operates in accordance with the print control program stored in the ROM 32 and controls the contents of the RAM 34 as the work area.

When the print sheet type information (media\_type), print sheet size information (Media\_size), print quality information (Print\_quality), print color information (Mono\_color), print offset position information (offset) and layout setting information (Layout\_type) are inputted from the data input section 31, the CPU 35 controls the print engine 33 in accordance with the various print settings.

When a print sheet of a type which is different from the print sheet type designated by the print sheet type information from the data input section 31 is prepared in the print engine 33, the CPU 35 controls the data input section 31 so as to generate a packet indicating that the print sheet type is different. In this case, when the print setting is different from the operation mode 2 parameters, the CPU 35 may carry out processing to indicate that the print setting is different, by using a display mechanism such as a lamp, not shown.

When a signal indicating that the bit is established as “device\_dependent” in the

print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information is inputted from the data input section 31, the CPU 35 carries out printing so as to realize the optimum print sheet type, print sheet size, print quality, print offset position or layout position.

Such CPU 35 carries out processing as shown in the flowchart of Fig.42 in accordance with the print control program.

In Fig.42, first, at step ST1, the data input section 31 of the printer device 5 receives a data packet generated in conformity with the IEEE 1394 standard from the data conversion section 13. In this case, the data input section 31 carries out processing in the transaction layer, link layer and physical layer conformable to the IEEE 1394 standard, thereby extracting static image data, which is a YCC image consisting of luminance information Y and color-difference information Cr, Cb. When the operation mode 2 parameters are included in the command packet, the data input section 31 outputs each print setting to the CPU 35.

At the next step ST2, the CPU 35 carries out screen dump processing for printing the whole display on the screen of the television unit 4.

At the next step ST3, the CPU 35 carries out raster processing with respect to the static image data on which screen dump processing has been performed at step ST2. That is, the CPU 35 carries out processing to convert the static image data to a dot format for transfer to the print engine 33.

At the next step ST4, the CPU 35 carries out expansion/contraction processing in accordance with the print size information with respect to the static image data on which raster processing has been performed at step ST2. That is, the CPU 35 carries out processing to change the size of the static image at the time of printing within a range designated by the user.

At the next step ST5, the CPU 35 carries out color adjustment processing in accordance with the print color information with respect to the static image data on which expansion/contraction processing has been performed at step ST4, thereby changing the static image data consisting of the luminance information and color-difference information into print data made up of R (Red), G (Green) and B (Blue) or black-and-white print data.

The relational expression of a pixel value with the color space designated in the Y (ITU-R BT.601-4) format and a pixel value with the color space designated by RGB is described as follows.

$$Y'_{601YCC} = 0.299 * R'_{RGB} + 0.587 * G'_{RGB} + 0.144 * B'_{RGB}$$

$$\begin{aligned} Cr'_{601YCC} &= 0.713 * (R'_{RGB} - Y'_{601YCC}) \\ &= 0.500 * R'_{RGB} - 0.419 * G'_{RGB} - 0.081 * B'_{RGB} \end{aligned}$$

$$\begin{aligned} Cb'_{601YCC} &= 0.564 * (B'_{RGB} - Y'_{601YCC}) \\ &= -0.169 * R'_{RGB} - 0.331 * G'_{RGB} + 0.500 * B'_{RGB} \end{aligned}$$

As an 8-bit value, these can be expressed as follows.

$$Y'_{601YCC\_8bit} = (219.0 * Y'_{601YCC}) + 16.0$$



$$Cb'_{601YCC\_8bit} = (224.0 * Cb'_{601YCC}) + 128.0$$

$$Cr'_{601YCC\_8bit} = (224.0 * Cr'_{601YCC}) + 128.0$$

This 8-bit value is transmitted as image data from the STB 3 to the printer device 5, and the 8-bit YCC value is converted to RGB at step ST5.

The relational expression of a pixel value with the color space designated in the Y (ITU-R BT.709-2) format and a pixel value with the color space designated by RGB is described as follows.

$$Y'_{709YCC} = 0.2126 * R'_{RGB} + 0.7152 * G'_{RGB} + 0.0722 * B'_{RGB}$$

$$Cb'_{709YCC} = 0.5389 * (B'_{RGB} - Y'_{709YCC})$$

$$Cr'_{709YCC} = 0.6350 * (R'_{RGB} - Y'_{709YCC})$$

As an 8-bit value, these can be expressed as follows.

$$Y'_{709YCC\_8bit} = (219.0 * Y'_{709YCC}) + 16.0$$

$$Cb'_{709YCC\_8bit} = (224.0 * Cb'_{709YCC}) + 128.0$$

$$Cr'_{709YCC\_8bit} = (224.0 * Cr'_{709YCC}) + 128.0$$

This 8-bit value is transmitted as image data from the STB 3 to the printer device 5, and the 8-bit YCC value is converted to RGB at step ST5.

At the next step ST6, the CPU 35 carries out processing to convert the print data, which is color-adjusted and made up of RGB, to the colors of cyan, magenta and yellow, thereby determining the ratio of cyan, magenta and yellow at each dot. At step ST7, the CPU 35 carries out dither processing.

Finally, at step ST8, the CPU 35 outputs the print data obtained by dither

processing to the print engine 33, thus carrying out print processing to drive the print engine 33 and draw the image onto the print object. In carrying out print processing, the CPU 35 sets the print sheet type, print sheet size, print quality, print color, print offset position and layout in accordance with the operation mode 2 parameters stored in the command packet from the data conversion section 13.

The processing of the CPU 23 when the printer device 5 prints the image data received by the STB 3 in the image printing system 1 constituted as described above will now be described with reference to Fig.43.

In the flowchart of Fig.43, first, at step ST11, as the user operates the operation button provided on the STB 3, an operation input signal to the effect that the dynamic image displayed on the television unit 4 is to be frozen is inputted to the CPU 23 of the STB 3. In response to this, the CPU 23 controls the display control section 19 to stop the output of the dynamic image data from the NTSC processing section 18 to the television unit 4, thus causing the television unit 4 to display a static image.

At the next step ST12, when an operation input signal to the effect that the static image data of a frame unit frozen at step ST11 and displayed on the television unit 4 is to be selected and printed by the printer device 5 is inputted from the operation input section 21, the CPU 23 controls the display control section 19, the MPEG processing section 16, and the demultiplexer section 14 to read the static image data of the frame unit stored in the display memory 20 into the image memory 15. Thus, the CPU 23 stores the static image data consisting of luminance information Y

and color-difference information Cr, Cb into the image memory 15.

At the next step ST13, the CPU 23 controls the data conversion section 13 so as to carry out connection setting between the STB 3 and the printer device 5 in conformity with the IEEE 1394 standard. Specifically, when a control signal to the effect that connection setting is to be carried out is inputted from the CPU 23, the data conversion section 13 generates a command packet and recognizes the plug with the data input section 31. In this case, the data conversion section 13 transmits to the data input section 31 of the printer device 5 a command packet having stored therein information indicating the transmission side. The data input section 31 of the printer device 5 recognizes the information indicating the transmission side plug and transmits to the data conversion section 13 a command packet having stored therein information indicating the receiving side plug to be asynchronously connected. Thus, the data conversion section 13 recognizes the information indicating the receiving side plug of the data input section 31 of the printer device 5, and the data input section 31 recognizes the information indicating the transmission side plug of the data conversion section 13 of the STB 3.

At the next step ST14, in accordance with an operation input signal, the CPU 23 generates a command packet designating the print sheet type, print sheet size, print quality, print color, print offset position, or layout setting at the time of printing the static image by the printer device 5, and outputs the command packet to the data input section 31. The CPU 23 also generates a command packet including a capture

command and outputs the command packet to the data input section 31. Thus, the CPU 23 makes print request.

At the next step ST15, the CPU 23 controls the demultiplexer section 14 and the data conversion section 13 to output to the printer device 5 the static image data to be printed by the printer device 5, thereby generating a data packet including the static image data stored in the image memory 15 and transmitting the data packet to the printer device 5.

As the printer device 5 has received a plurality of data packets including the information indicating the receiving side plug and thus determines that it has received all the data of the static image data, the printer device 5 causes the CPU 35 to carry out the processing shown in Fig.42, thereby printing the image represented by the static image data in accordance with the designated print size or the like.

An example of transmitting/receiving the asynchronous packet 100 between the STB 3 and the printer device 5 and printing the static image data by the printer 5 will now be described with reference to Fig.44.

In Fig.44, before starting print processing, the data conversion section 13 transmits a command packet (JOB\_QUEUE) S11 to the printer device 5 so as to indicate that there is a job of printing one static image, and receives a response packet S12 for this command packet.

The data conversion section 13 transmits to the printer device 5 a command packet S13 which designates the operation mode indicating the type and size of the

print sheet, print quality, color (monochrome/color) for print processing and printing position at the time of printing by the printer device 5, or which designates the operation mode 2 parameters including the print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information, and then receives a response packet S14 for that command packet. In this case, on the basis of the response from the printer device 5, the data conversion section 13 discriminates whether the printer device 5 is capable of accepting the operation mode 2 parameters or not.

Then, the data conversion section 13 carries out plug setting for transmitting the static image data to the data input section 31. Specifically, the data conversion section 13 first transmits a command packet S15 having stored therein an ALLOCATE command to the data input section 31 so as to carry out setting of the receiving side plug, and then receives a response packet S16 for that command.

The data conversion section 13 also transmits a command packet S17 having stored therein an ATTACH command indicating that the plug for receiving the data packet including the static image data to be printed by the printer device 5 should be set and transmission/reception of the data packet should be carried out, and then receives a response packet S18 for that command packet.

Then, the data conversion section 13 transmits a command packet S19 including a capture command. In the command packet S19, information indicating the transmission side plug on the side of the data conversion section 13 (source\_plug) is

stored. Thus, the data input section 31 recognizes the transmission side plug of the data conversion section 13.

The data input section 31 transmits a packet S20 including information setting oAPR (output Asynchronous Port Register) to the data conversion section 13. In the packet S20, information indicating the receiving side plug of the data input section 31 (dest\_plug) is stored. In this case, the data input section 31 transmits the packet S20 including the information indicating the transmission side plug recognized by receiving the command packet S19. Then, the data conversion section 13 recognizes the receiving side plug of the data input section 31.

The data conversion section 13 transmits to the data input section 31 a data packet S21 having the static image data of a YCC image stored in the data portion 102. In this case, the data conversion section 13 divides the static image data into predetermined data quantities and transmits a plurality of data packets S21.

Then, the data conversion section 13 transmits to the data input section 31 a response packet S22 including information related to iAPR (input Asynchronous Port Register) of a flow control register of the transmission side plug.

The data input section 31 transmits to the data conversion section 13 a command packet S23 indicating that the capture command has been accepted.

In response to this, the data conversion section 13 transmits a command packet S24 including a DETACH command indicating that the connection with the printer device 5 should be canceled, and receives a response packet S25 from the data input

section 31.

The data conversion section 13 transmits a command packet S25 including a RELEASE command to the data input section 31 of the printer device 5, and receives a response packet S26 from the data input section 31.

Then, the data conversion section 13 transmits to the data input section 31 a command packet (JOB\_QUEUE) S28 indicating that the sequence indicating the job of printing the static image is completed, and receives a response packet S29 for that command packet.

Thus, with such image printing system 1, even when the STB 3 and the printer device 5 are connected with each other in conformity with the IEEE 1394 standard, the asynchronous packet 100 including the print sheet type information, print sheet size information, print quality information, print color information, print offset position information and layout setting information is transmitted to the printer device 5, and detailed print setting can be carried out in response to the request from the user.

Specifically, with the image printing system 1, the user can generate an operation input signal requesting the print quality, print speed or the like, and can cause the printer device 5 to carry out print processing in response to the operation input signal.

Also, with the image printing system 1, even in the case where a print sheet which requires precise designation of the printing position for printing at the accurate position such as a seal with a slit formed thereon is used, a command packet including

the print sheet type information and print offset position information or the like is transmitted from the data conversion section 13 to the data input section 31, and accurate print processing can be carried out by the printer device 5.

Moreover, with the image printing system 1, the print offset position information enables designation of the print start position by designating the position of the origin at the upper left part of the print sheet within a range of 00.0 to 99.9 mm from the top and left ends of the sheet. Therefore, minute control of the print start position is made possible.

The printing position within the effective print range is designated by the layout setting information or the like. The effective print range might be deviated in some cases due to the difference in the sheet feeding system such as hand-feeding or cassette-feeding. Even in the case where the mechanical accuracy for sheet feeding is thus changed by the use state of the printer device 5 dependent on the user, the aged deterioration of the printer device 5, the thickness of the print sheet, the surface state of the print sheet, or the size of the print sheet, the print start position can be minutely set in accordance with the print offset position information and printing can be carried out at the accurate position.

Also, with the image printing system 1, optimum printing can be carried out in accordance with the type of the sheet on the side of the STB 3. Specifically, with the image printing system 1, the print speed can be adjusted in accordance with the print sheet. For example, when a seal is used as the print sheet, printing is carried out at a



lower speed than when a normal sheet is used.

Moreover, with the image printing system 1, even in the case where the printer device 5 is set in the state which is different from the request from the user, the CPU 35 of the printer device 5 carries out control so as to transmit a packet command to that effect from the data input section 31 to the data conversion section 13, thereby notifying the user.

In the above description of the image printing system 1, the asynchronous packet 100 including non-compressed static image data is transmitted from the STB 3 to the printer device 5. However, the static image data may be compressed in accordance with the JPEG system by the MPEG processing section 16 and the asynchronous packet 100 including the compressed static image data may be transmitted and received. With such image printing system 1, since the quantity of data to be transmitted can be reduced, data transfer and print processing at a higher speed can be realized.

Also, in the above description of the image printing system 1, the data conversion section 13 and the data input section 31, which are interface circuits conformable to the IEEE 1394 standard, are provided in the STB 3 and the printer device 5, respectively. However, other interface circuits such as USB may also be used. That is, with the image printing system 1 including the STB 3 and the printer device 5 which have USB, packets in the digital system can be transmitted/received between the STB 3 and the printer device 5 and a precise image can be printed by the

printer device 5.

Meanwhile, the FCP and AV/C protocol prescribe information indicating how many images should be printed on one page (`number_of_pics`) in the operation mode 1 command for print setting.

For example, in the case of producing an index of a CD album, a list of music tune titles with an image size contracted to 1/4 is to be printed in a left half portion of the sheet and an image with an image size contracted to 1/4 is to be printed in a right half portion of the sheet, as shown in Fig.45. In this case, such printing is made possible by setting allocation of four images on one sheet in accordance with “`number_of_pics`” of the operation mode 1 command and then alternately transmitting the title list and the image to the printer device 5 in accordance with the capture command.

However, if a certain album does not have a title list, the title list of that album cannot be transmitted to printer device 5. Then, as shown in Fig.46, the image of that album is moved forward and printed in the left half portion of the sheet, where the title list should be printed.

Thus, the STB 3 and the printer device 5 carry out the following setting so as to provide a blank area in an arbitrary print area when printing a plurality of images on one page, as shown in Fig.47.

To provide a blank area, the image type (`image_format_specifier`) is set (e.g., sRGB row) in the capture command, but the quantity of data to be transmitted

(data\_size), the number of pixels in the X-direction (image\_size\_x) and the number of pixels in the Y-direction (image\_size\_y) are all set to 0, as shown in Fig.48. Specifically, in the case of producing a blank area, the STB 3 sets a capture command as shown in Fig.48 in accordance with the operation input from the user and transmits the capture command to the printer device 5. Then, the printer device 5, having received the capture command thus set, makes a blank in the corresponding area on the basis of the setting and continues printing from the next area. In this case, the image type (image\_format\_specifier) may be "sRGB row" as shown in Fig.49, other than "Don't Care" as shown in Fig.48.

As another example, the format type of "Null Object" is added to the image of the image type (image\_format\_specifier) set by the capture command, as shown in Fig.50. "Unit Plug defined" newly shown in Fig.50 is stored in the case of transmitting an isochronous packet with an isochronous plug designated as "source\_plug" of the capture command. "Don't care" means that the transmission side does not care the image type. That is, the transmission side does not care about the contents of the transmitted object, i.e., the image type of the captured image. In this case, even when certain processing is required on the printer side, such processing is handled by the AV/C command, and default setting is carried out on the printer side, if necessary, or such processing is handled by other commands. Thus, in the case of providing a blank area as in the present invention, though it is necessary to provide an area with a designated size, substantially no image contents exist. Therefore, it means that the

image size and the number of pixels in the X-direction and Y-direction are zero, and one capture can be processed as a blank.

In the case of producing a blank area, the STB 3 sets “Null Object” as the image type (image\_format\_specifier) of the capture command in accordance with the operation input from the user, and transmits the capture command to the printer device 5. Then, the printer device 5, having received the capture command thus set, makes a blank in the corresponding area on the basis of the setting and continues printing from the next area.

As still another example, skip information for producing a blank area is stored in “subfunction” of the capture command. For example, information expressed by hexadecimal 02 and referred to as “skip” as shown in Fig.51 is stored. In the case of producing a blank area, the STB 3 stores hexadecimal 02 into “subfunction” of the capture command in accordance with the operation input from the user and transmits the capture command to the printer device 5. Then, the printer device 5, having received the capture command thus set, makes a blank in the corresponding area on the basis of the setting and continues printing from the next area. The information set in “subfunction” may be, for example, information expressed by hexadecimal 01 and referred to as “receive”, information expressed by hexadecimal 03 and referred to as “resume”, and information expressed by hexadecimal 04 and referred to as “query”, as well as the above-mentioned information of hexadecimal 02. The information “receive” is stored in “subfunction” when giving an image data reception instruction

by the capture command. In the case of transmitting the image data, the STB 3 stores "receiver" in "subfunction" of the capture command and gives an image data reception instruction to the printer device 5. The information "resume" is stored in "subfunction" when confirming the quantity of image data already transmitted to the printer device 5 in the case where bus reset is carried out on the IEEE 1394 interface. The information "query" is stored in "subfunction" when wishing to know the possible setting range of the operation mode 2 parameters of the printer device 5.

As described above, with the image printing system 1, in the case of printing a plurality of images on one page, a blank area can be provided in a part of the page. Therefore, with the image printing system 1, a contracted image can be allocated at an arbitrary position on the print sheet. Also, in the case where only a small number of capture commands are transmitted with respect to the number of allocated images, it can be easily determined whether a blank area should be provided in the corresponding area or there is an error.

### Industrial Applicability

With the image processing device and method according to the present invention, since print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image into the image to be printed on the print sheet is transmitted, a blank area can be provided in a part of the sheet in the case of printing a plurality of images on

one page. Thus, according to the present invention, a contracted image can be allocated at an arbitrary position on the print sheet.

With the printing device and method according to the present invention, since printing is carried out using print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image into the image to be printed on the print sheet, a blank area can be provided in a part of the sheet in the case of printing a plurality of images on one page. Thus, according to the present invention, a contracted image can be allocated at an arbitrary position on the print sheet.

With the image printing system and method according to the present invention, since print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image into the image to be printed on the print sheet is transmitted, a blank area can be provided in a part of the sheet in the case of printing a plurality of images on one page. Thus, according to the present invention, a contracted image can be allocated at an arbitrary position on the print sheet.

With the recording medium according to the present invention, since print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image into the image to be printed on the print sheet is transmitted, a blank area can be provided in a part of the sheet in the case of printing a plurality of images on one page. Thus,

according to the present invention, a contracted image can be allocated at an arbitrary position on the print sheet.

With the recording medium according to the present invention, since printing is carried out using print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image into the image to be printed on the print sheet, a blank area can be provided in a part of the sheet in the case of printing a plurality of images on one page. Thus, according to the present invention, a contracted image can be allocated at an arbitrary position on the print sheet.

09031694-071901

## CLAIMS

1. An image processing device comprising:

image processing means for performing image processing on an image signal inputted from outside and thus generating image data;

control information generation means for generating print control information including information indicating the number of print images on one page of a print sheet; and

output means for including the image data generated by the image processing means and the print control information generated by the control information generation means into a packet conformable to the IEEE (the Institute of Electrical and Electronics Engineers) 1394 standard and outputting the packet to a printing device;

the control information generation means generating print control information including information which includes a blank image in the image to be printed on the print sheet.

2. An image processing method comprising the steps of:

performing image processing on an image signal inputted from outside and thus generating image data;

generating print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank area in the image to be printed on the print sheet; and



including the generated image data and the print control information into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device.

3. An image processing method comprising the steps of:

performing image processing on an image signal inputted from outside and thus generating image data;

generating a command instructing start of a print job with respect to the generated image data, a command including information indicating the number of print images on one page of a print sheet, and a capture command including print control information with respect to the generated image data:

including the generated image data and the respective commands into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device; and

in the case where a blank image is included in an image area to be printed on the print sheet, setting the data quantity of image data and the number of pixels in an X-direction and a Y-direction at zero as print control information with respect to the blank image and setting the capture command at a value indicating that the image type of the image data is not considered.

4. A printing device comprising:

input means to which image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the

number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet are inputted; and

printing means for printing an image represented by the image data inputted to the input means in accordance with the print control information;

the printing means setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image is inputted.

5. A printing method comprising the steps of:

receiving input of image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet;

printing an image represented by the inputted image data in accordance with the print control information; and

setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image in the image to be printed on the print sheet is inputted.

6. A printing method comprising the steps of:

performing image processing on an image signal inputted from outside and thus generating image data;

receiving input of the image data included in a packet conformable to the IEEE 1394 standard, a command instructing start of a print job with respect to the image data, a command including information indicating the number of print images on one page of a print sheet, and a capture command including print control information with respect to the generated image data; and

setting an image area to be printed on the print sheet as a blank area in the case where the capture command is inputted which sets the data quantity of image data and the number of pixels in an X-direction and a Y-direction at zero as print control information and which is set at a value indicating that the image type of the image data is not considered

7. An image printing system comprising:

a print processing device including image processing means for performing image processing on an image signal inputted from outside and thus generating image data, control information generation means for generating print control information including information indicating the number of print images on one page of a print sheet, and output means for including the image data generated by the image processing means and the print control information generated by the control information generation means into a packet conformable to the IEEE 1394 standard and outputting the packet, the control information generation means generating print control information including information which includes a blank image in the image to be printed on the print sheet; and

a printing device including input means to which image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet are inputted, and printing means for printing an image represented by the image data inputted to the input means in accordance with the print control information, the printing means setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image is inputted.

8. An image printing method comprising the steps of:

performing image processing on an image signal inputted from outside and thus generating image data;

generating print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet;

including the generated image data and the print control information into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device;

receiving the image data included in a packet conformable to the IEEE 1394 standard and the print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a

blank image in the image to be printed on the print sheet;

printing an image represented by the received image data in accordance with the print control information; and

setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image in the image to be printed on the print sheet is inputted.

9. A recording medium having an image processing program stored therein, the image processing program comprising the steps of:

performing image processing on an image signal inputted from outside and thus generating image data;

generating print control information including information indicating the number of print images on one page of a print sheet and information indicating inclusion of a blank image in the image to be printed on the print sheet; and

including the generated image data and the print control information into a packet conformable to the IEEE 1394 standard and outputting the packet to a printing device.

10. A recording medium having a printing program stored therein, the printing program comprising the steps of:

receiving input of image data included in a packet conformable to the IEEE 1394 standard and print control information including information indicating the number of print images on one page of a print sheet and information indicating

inclusion of a blank image in the image to be printed on the print sheet;

printing an image represented by the inputted image data in accordance with the print control information; and

setting an image area to be printed on the print sheet as a blank area in the case where the print control information including information indicating inclusion of a blank image in the image to be printed on the print sheet is inputted.

## ABSTRACT

A capture command in the AV/C protocol of the IEEE 1394 standard is set as follows.

The quantity of data to be transmitted (`data_size`), the number of pixels in the X-direction (`image_size_x`) and the number of pixels in the Y-direction (`image_size_y`) are all set to 0. The image type (`image_format_specifier`) is set to “Don’t Care”.

A printer device, having received such a capture command, makes a blank in the corresponding print area without printing the image and then prints the next image.

1 : IT IS RAINY TODAY  
2 : IT WILL BE CLOUDY  
TOMORROW  
3 : IT WAS WARM  
YESTERDAY  
4 : XXXXXX  
5 : YYYYYY  
6 : ZZZZZZ  
7 : XXXXXX  
8 : YYYYYY  
9 : ZZZZZZ  
10 : XXXXXX  
11 : YYYYYY  
12 : ZZZZZZ






FIG.1






FIG.2




FIG.3




FIG.4

100




FIG.5




FIG.6




FIG.7

	pixel_x	pixel_y	interlaced/ progressive	pixel format	screen aspect ratio	pixel aspect ratio	based standard	image size
1080_422_16×9	1920	1080	interlaced/ progressive	YCbCr 4:2:2	16:9	1:1	ITU-R BT. 709-2	3.96MB
1080_420_16×9	1920	1080	interlaced/ progressive	YCbCr 4:2:0	16:9	1:1	ITU-R BT. 709-2	2.97MB
720_422_16×9	1280	720	progressive	YCbCr 4:2:2	16:9	1:1	ANSI/SMP TE 296 M-1997	1.76MB
720_420_16×9	1280	720	progressive	YCbCr 4:2:0	16:9	1:1	ANSI/SMP TE 296 M-1997	1.32MB
576_422_4×3	720	576	interlaced/ progressive	YCbCr 4:2:2	4:3	1.07:1	ITU-R BT.1203	810KB
576_420_4×3	720	576	interlaced/ progressive	YCbCr 4:2:0	4:3	1.07:1	ITU-R BT.1203	608KB
480_422_16×9	720	480	interlaced/ progressive	YCbCr 4:2:2	16:9	1.91:1	ITU-R BT. 709-2	675KB
480_420_16×9	720	480	interlaced/ progressive	YCbCr 4:2:0	16:9	1.91:1	ITU-R BT. 709-2	506KB
480_422_4×3	720	480	interlaced/ progressive	YCbCr 4:2:2	4:3	0.89:1	ITU-R BT.601-4	675KB
480_420_4×3	720	480	interlaced/ progressive	YCbCr 4:2:0	4:3	0.89:1	ITU-R BT.601-4	506KB

FIG.8

	msb						lsb
opcode	CAPTURE(42 <sub>16</sub> )						
operand [0]	subfunction						
operand [1]	source_subunit_type				source_subunit_ID		
operand [2]	source_plug						
operand [3]	status						
operand [4]	dest_plug						
operand [5]	print_job_ID						
:							
operand [16]							
operand [17]	data_size						
operand [18]							
operand [19]							
operand [20]							
operand [21]	image_size_x						
operand [22]							
operand [23]	image_size_y						
operand [24]							
operand [25]	image_format_specifier						
operand [26]							
operand [27]	reserved						
operand [28]							
operand [29]							
operand [30]	Next_pic						
operand [31]	Next_page						
operand [32]							

FIG.9

value	Type	Meaning
20 <sub>16</sub>	1080i _ 422chunky _ 16×9	
21 <sub>16</sub>	1080p _ 422chunky _ 16×9	
22 <sub>16</sub>	720p _ 422chunky _ 16×9	
23 <sub>16</sub>	480i _ 422chunky _ 16×9	
24 <sub>16</sub>	480p _ 422chunky _ 16×9	
25 <sub>16</sub>	480i _ 422chunky _ 4×3	
26 <sub>16</sub>	480p _ 422chunky _ 4×3	
28 <sub>16</sub>	1080i _ 422liner _ 16×9	
29 <sub>16</sub>	1080p _ 422liner _ 16×9	
2A <sub>16</sub>	720p _ 422liner _ 16×9	
2B <sub>16</sub>	480i _ 422liner _ 16×9	
2C <sub>16</sub>	480p _ 422liner _ 16×9	
2D <sub>16</sub>	480i _ 422liner _ 4×3	
2E <sub>16</sub>	480p _ 422liner _ 4×3	
30 <sub>16</sub>	1080i _ 420planer _ 16×9	
31 <sub>16</sub>	1080p _ 420planer _ 16×9	
32 <sub>16</sub>	720p _ 420planer _ 16×9	
33 <sub>16</sub>	480i _ 420planer _ 16×9	
34 <sub>16</sub>	480p _ 420planer _ 16×9	
35 <sub>16</sub>	480i _ 420planer _ 4×3	
36 <sub>16</sub>	480p _ 420planer _ 4×3	
38 <sub>16</sub>	1080i _ 420liner _ 16×9	
39 <sub>16</sub>	1080p _ 420liner _ 16×9	
3A <sub>16</sub>	720p _ 420liner _ 16×9	
3B <sub>16</sub>	480i _ 420liner _ 16×9	
3C <sub>16</sub>	480p _ 420liner _ 16×9	
3D <sub>16</sub>	480i _ 420liner _ 4×3	
3E <sub>16</sub>	480p _ 420liner _ 4×3	
60 <sub>16</sub>	Text(ASCII)	MD-clip ASCII
61 <sub>16</sub>	Text(ISO8859-1)	MD-clip modified ISO8859-1
62 <sub>16</sub>	Text(Music Shifted JIS)	MD-clip Music Shifted JIS

FIG.10



Value(MSB)	Value(LSB)	Type	Meaning
00 <sub>16</sub>			sRGB raw
	00 <sub>16</sub>	sRGB raw	
	01 <sub>16</sub>	sRGB raw,quadlet	
01 <sub>16</sub>			YCC raw
	0X <sub>16</sub>	YCC4:2:2 raw/chunky	
	1X <sub>16</sub>	YCC4:2:2 raw/liner	
	8X <sub>16</sub>	YCC4:2:0 raw/chunky	
	9X <sub>16</sub>	YCC4:2:0 raw/liner	
	X0 <sub>16</sub>	Pixel ratio 1.00×1.00 / ITU-R BT.709-2 / interlace	
	X1 <sub>16</sub>	Pixel ratio 1.19×1.00 / ITU-R BT.709-2 / interlace	
	X2 <sub>16</sub>	Pixel ratio 0.89×1.00 / ITU-R BT.709-2 / interlace	
	X3 <sub>16</sub>	Pixel ratio 0.89×1.00 / ITU-R BT.601-4 / interlace	
	X4 <sub>16</sub>	Pixel ratio 1.07×1.00 / ITU-R BT.1203 / interlace	
	X8 <sub>16</sub>	Pixel ratio 1.00×1.00 / ITU-R BT.709-2 / progressive	
	X9 <sub>16</sub>	Pixel ratio 1.19×1.00 / ITU-R BT.709-2 / progressive	
	XA <sub>16</sub>	Pixel ratio 0.89×1.00 / ITU-R BT.709-2 / progressive	
	XB <sub>16</sub>	Pixel ratio 0.89×1.00 / ITU-R BT.601-4 / progressive	DCF Object
	XC <sub>16</sub>	Pixel ratio 1.07×1.00 / ITU-R BT.1203 / progressive	
10 <sub>16</sub>		Exif 2.1	
	00 <sub>16</sub>	JFIF	
	01 <sub>16</sub>	TIFF	
	02 <sub>16</sub>	JPEG	
	0F <sub>16</sub>		
80 <sub>16</sub> ~8F <sub>16</sub>	00 <sub>16</sub> ~FF <sub>16</sub>	Vendor Dependent format	
FE <sub>16</sub>			Special meaning
	00 <sub>16</sub>	Unit Plug defined	
	01 <sub>16</sub>	don't care	

FIG.11

$Y_1(L_1)$	$Y_2(L_1)$	$Cb_1(L_1)$	$Cr_1(L_1)$
$Y_3(L_1)$	$Y_4(L_1)$	$Cb_3(L_1)$	$Cr_3(L_1)$
$\vdots$			
$Y_{N-1}(L_1)$	$Y_N(L_1)$	$Cb_{N-1}(L_1)$	$Cr_{N-1}(L_1)$
$Y_1(L_2)$	$Y_2(L_2)$	$Cb_1(L_2)$	$Cr_1(L_2)$
$\vdots$			
$Y_{N-1}(L_M)$	$Y_N(L_M)$	$Cb_{N-1}(L_M)$	$Cr_{N-1}(L_M)$

FIG.12

$Y_1(L_1)$	$Y_2(L_1)$	$Y_1(L_2)$	$Y_2(L_2)$
$Cb_1(L_1)$	$Cr_1(L_1)$	$Y_3(L_1)$	$Y_4(L_1)$
$Y_3(L_2)$	$Y_4(L_2)$	$Cb_3(L_1)$	$Cr_3(L_1)$
$\vdots$			
$Y_{N-3}(L_{M-1})$	$Y_{N-2}(L_{M-1})$	$Y_{N-3}(L_M)$	$Y_{N-2}(L_M)$
$Cb_{N-3}(L_{M-1})$	$Cr_{N-3}(L_{M-1})$	$Y_{N-1}(L_{M-1})$	$Y_N(L_{M-1})$
$Y_{N-1}(L_M)$	$Y_N(L_M)$	$Cb_{N-1}(L_{M-1})$	$Cr_{N-1}(L_{M-1})$

FIG.13

FIG. 12

$Y_1(L_1)$	$Y_2(L_1)$	$Y_3(L_1)$	$Y_4(L_1)$
$\vdots$			
$Y_{N-3}(L_1)$	$Y_{N-2}(L_1)$	$Y_{N-1}(L_1)$	$Y_N(L_1)$
$Cb_1(L_1)$	$Cr_1(L_1)$	$Cb_3(L_2)$	$Cr_3(L_1)$
$\vdots$			
$Cb_{N-3}(L_M)$	$Cr_{N-3}(L_1)$	$Cb_{N-1}(L_1)$	$Cr_{N-1}(L_1)$
$Y_1(L_2)$	$Y_2(L_2)$	$Y_3(L_1)$	$Y_4(L_1)$
$\vdots$			
$Cb_{N-3}(L_M)$	$Cr_{N-3}(L_M)$	$Cb_{N-1}(L_M)$	$Cr_{N-1}(L_M)$

FIG.14

$Y_1(L_1)$	$Y_2(L_1)$	$Y_3(L_1)$	$Y_4(L_1)$
		$\vdots$	
$Y_{N-3}(L_1)$	$Y_{N-2}(L_1)$	$Y_{N-1}(L_1)$	$Y_N(L_1)$
$Y_1(L_2)$	$Y_2(L_2)$	$Y_3(L_2)$	$Y_4(L_2)$
		$\vdots$	
$Y_{N-3}(L_2)$	$Y_{N-2}(L_2)$	$Y_{N-1}(L_2)$	$Y_N(L_2)$
$Cb_1(L_1)$	$Cr_1(L_1)$	$Cb_3(L_1)$	$Cr_3(L_1)$
		$\vdots$	
$Cb_{N-3}(L_1)$	$Cr_{N-3}(L_1)$	$Cb_{N-1}(L_1)$	$Cr_{N-1}(L_1)$
$Y_1(L_3)$	$Y_2(L_3)$	$Y_3(L_3)$	$Y_4(L_3)$
		$\vdots$	
$Cb_{N-3}(L_{M-1})$	$Cr_{N-3}(L_{M-1})$	$Cb_{N-1}(L_{M-1})$	$Cr_{N-1}(L_{M-1})$

FIG.15

FIG. 15

Address Offset	1 <sup>st</sup> byte	2 <sup>nd</sup> byte	3 <sup>rd</sup> byte	4 <sup>th</sup> byte
00 00 00 00 <sub>16</sub>	Y1(L1)	Y2(L1)	Cb1(L1)	Cr1(L1)
00 00 00 04 <sub>16</sub>	Y3(L1)	Y4(L1)	Cb3(L1)	Cr3(L1)
⋮	⋮			
00 00 05 9C <sub>16</sub>	Y719(L1)	Y720(L1)	Cb719(L1)	Cr719(L1)
00 00 05 A0 <sub>16</sub>	Y1(L2)	Y2(L2)	Cb1(L2)	Cr1(L2)
⋮	⋮			
00 0A 8B FC <sub>16</sub>	Y719(L480)	Y720(L480)	Cb719(L480)	Cr719(L480)

FIG.16

Address Offset	1 <sup>st</sup> byte	2 <sup>nd</sup> byte	3 <sup>rd</sup> byte	4 <sup>th</sup> byte
00 00 00 00 <sub>16</sub>	Y1(L1)	Y2(L1)	Y1(L2)	Y2(L2)
00 00 00 04 <sub>16</sub>	Cr1(L1)	Cr1(L1)	Y3(L1)	Y4(L1)
00 00 00 08 <sub>16</sub>	Y3(L2)	Y4(L2)	Cb3(L1)	Cr3(L1)
⋮	⋮			
00 07 E8 F8 <sub>16</sub>	Cb717(L479)	Cr717(L479)	Y719(L479)	Y720(L479)
00 07 E8 FC <sub>16</sub>	Y719(L480)	Y720(L480)	Cb719(L479)	Cr719(L479)

FIG.17

09/831694-07-F01

Address Offset	1 <sup>st</sup> byte	2 <sup>nd</sup> byte	3 <sup>rd</sup> byte	4 <sup>th</sup> byte
00 00 00 00 <sub>16</sub>	Y1(L1)	Y2(L1)	Y3(L1)	Y4(L1)
⋮	⋮			
00 00 02 CF <sub>16</sub>	Y717(L1)	Y718(L1)	Y719(L1)	Y720(L1)
00 00 02 D0 <sub>16</sub>	Cb1(L1)	Cr1(L1)	Cb3(L1)	Cr3(L1)
⋮	⋮			
00 00 05 9F <sub>16</sub>	Cb717(L1)	Cr717(L1)	Cb719(L1)	Cr719(L1)
00 00 05 A0 <sub>16</sub>	Y1(L2)	Y2(L2)	Y3(L2)	Y4(L2)
⋮	⋮			
00 0A 8B FC <sub>16</sub>	Cb717(L480)	Cr717(L480)	Cb719(L480)	Cr719(L480)

FIG.18

FIG. 18

Address Offset	1 <sup>st</sup> byte	2 <sup>nd</sup> byte	3 <sup>rd</sup> byte	4 <sup>th</sup> byte
00 00 00 00 <sub>16</sub>	Y1(L1)	Y2(L1)	Y3(L1)	Y4(L1)
⋮	⋮			
00 00 02 CF <sub>16</sub>	Y717(L1)	Y718(L1)	Y719(L1)	Y720(L1)
00 00 02 D0 <sub>16</sub>	Y1(L2)	Y2(L2)	Y3(L2)	Y4(L2)
⋮	⋮			
00 00 05 9F <sub>16</sub>	Y717(L2)	Y718(L2)	Y719(L2)	Y720(L2)
00 00 05 A0 <sub>16</sub>	Cb1(L1)	Cr1(L1)	Cb3(L1)	Cr3(L1)
⋮	⋮			
00 00 08 6F <sub>16</sub>	Cb717(L1)	Cr717(L1)	Cb719(L1)	Cr719(L1)
00 00 08 70 <sub>16</sub>	Y1(L3)	Y2(L3)	Y3(L3)	Y4(L3)
⋮	⋮			
00 07 E8 FC <sub>16</sub>	Cb717(L479)	Cr717(L479)	Cb719(L479)	Cr719(L479)

FIG.19



	msb						lsb
opcode	OPERATION MODE2(51 <sub>16</sub> )						
operand [0]	subfunction						
operand [1]	status						
operand [2]	reserved						
operand [3]							
operand [4]							
operand [5]	print_job_ID						
⋮							
operand [16]							
operand [17]	Operation_mode2_parameters						
⋮							
operand [31]							

FIG.20

Value	Symbol	Meaning
01 <sub>16</sub>	get	Get the current operation modes
02 <sub>16</sub>	set	Set the specified operation modes
03 <sub>16</sub>	query	Get the supported operation modes
Other values	–	Reserved

FIG.21

Address Offset	Contents
00 <sub>16</sub>	media_type
01 <sub>16</sub>	Media_size
02 <sub>16</sub>	
03 <sub>16</sub>	
04 <sub>16</sub>	reserved
05 <sub>16</sub>	Print_quality
06 <sub>16</sub>	Mono_color
07 <sub>16</sub>	offset
08 <sub>16</sub>	
09 <sub>16</sub>	
0A <sub>16</sub>	
0B <sub>16</sub>	Layout_type
0C <sub>16</sub>	
0D <sub>16</sub>	
0E <sub>16</sub>	

FIG.22

address offset	msb							lsb
00 <sub>16</sub>	device_ dependent	Plain_ paper <sub>1</sub>	Bond_ paper	Special_ paper	Photo_ paper	Transpare ncy_film	Reserved	

FIG.23

Symbol	Meaning
device_dependent	The image output will be sized as device dependent. (Mandatory)
Plain_paper	NORMAL PAPER
Bond_paper	SEAL
Special_paper	SPECIAL PAPER
Photo_paper	PHOTOGRAPHIC PAPER
Transparency_film	OHP FILM

FIG.24

FIG. 24

address offset	msb								lsb
00 <sub>16</sub>	device_ dependent	A5	A4	B5	Executive	Letter	Legal	Reserved	
01 <sub>16</sub>	Hagaki	Oufuku- Hagaki	A6	Index_4×6	Index_5×8	A3	B4	Legal_11X 17	
02 <sub>16</sub>	Commerci all0_portr alt	Commerci all0_land cape	DL	C6	A2	Custom	reserved		

FIG.25

Symbol	Meaning
Device_dependent	The image output will be sized as device dependent. (Mandatory)
A5	ISO and JIS A5
A4	ISO and JIS A4
B5	JIS B5
Executive	US Executive
Letter	US Letter
Legal	US Legal
Hagaki	POSTCARD
Oufuku_hagaki	DOUBLE POSTAL CARD
A6	ISO and JIS A6 Card
Index_4×6	US Index Card4"×6"
Index_5×8	US Index Card5"×3"
A3	ISO A3
B4	B4
Legal_11×17	Legal 11×17
Commercial10_portrait	US Comercial#10(portrait)
Commercial10_landscape	US Comercial#10(landscape)
DL	International DL
C6	International C6
A2	US A2
Custom	Custom paper

FIG.26

address offset	msb	other	letter	legal					lsb
00 <sub>16</sub>	device-dependent				reserved				
01 <sub>16</sub>	na_10×13_envelope	na_9×12_envelope	na_number_ID_envelope	na_7×9_envelope	na_9×11_envelope	na_10×14_envelope	na_6×9_envelope	na_10×15_envelope	
02 <sub>16</sub>	a	b	c	d	e	reserved			
03 <sub>16</sub>	iso a0	iso a1	iso a2	iso a3	iso a4	iso a5	iso a6	iso a7	
04 <sub>16</sub>	iso a8	iso a9	iso a10	Reserved					
05 <sub>16</sub>	iso b0	iso b1	iso b2	iso b3	iso b4	iso b5	iso b6	iso b7	
06 <sub>16</sub>	iso b8	iso b9	iso b10	Reserved					
07 <sub>16</sub>	iso c0	iso c1	iso c2	iso c3	iso c4	iso c5	iso c6	iso c7	
08 <sub>16</sub>	iso c8	iso designated	reserved						
09 <sub>16</sub>	jis b0	jis b1	jis b2	jis b3	jis b4	jis b5	jis b6	jis b7	
0A <sub>16</sub>	jis b8	jis b9	jis b10	reserved					
0B <sub>16</sub>	index_4×6	index_5×8	reserved		Japanese_hagaki	Japanese_oufuku_hagaki	reserved		

FIG.27



Value	Symbol	Meaning	Width	Height
00 <sub>16</sub>	device_dependent	The paper alze will be used as device dependent	—	—
01 <sub>16</sub>	other	other		
10 <sub>16</sub>	letter	North American letter size	8.5 inch	11 inch
11 <sub>16</sub>	legal	North American letter size	8.5 inch	14 inch
20 <sub>16</sub>	na_10×13_envelope	North American 10×13 envelope size	10 inch	13 inch
21 <sub>16</sub>	na_9×12_envelope	North American 9×12 envelope	9 inch	12 inch
22 <sub>16</sub>	na_number_10_envelope	North American number 10business envelope	4.125 inch	9.5 inch
23 <sub>16</sub>	na_7×9_envelope	North American 7×9	7 inch	9 inch
24 <sub>16</sub>	na_9×11_envelope	North American 9×11	9 inch	11 inch
25 <sub>16</sub>	na_10×14_envelope	North American 10×14 envelope	10 inch	14 inch
26 <sub>16</sub>	na_6×9_envelope	North American 6×9 envelope	6 inch	9 inch
27 <sub>16</sub>	na_10×15_envelope	North American 10×15 envelope	10 inch	15 inch
30 <sub>16</sub>	a	engineering A	8.5 inch	11 inch
31 <sub>16</sub>	b	engineering B	11 inch	17 inch
32 <sub>16</sub>	c	engineering C	17 inch	22 inch
33 <sub>16</sub>	d	engineering D	22 inch	34 inch
34 <sub>16</sub>	e	engineering E	34 inch	44 inch
40 <sub>16</sub>	iso a0	ISO A0	841mm	1189mm
41 <sub>16</sub>	iso a1	ISO A1	594mm	841mm
42 <sub>16</sub>	iso a2	ISO A2	420mm	594mm
43 <sub>16</sub>	iso a3	ISO A3	297mm	420mm
44 <sub>16</sub>	iso a4	ISO A4	210mm	297mm
45 <sub>16</sub>	iso a5	ISO A5	148mm	210mm
46 <sub>16</sub>	iso a6	ISO A6	105mm	148mm
47 <sub>16</sub>	iso a7	ISO A7	74mm	105mm
48 <sub>16</sub>	iso a8	ISO A8	52mm	74mm
49 <sub>16</sub>	iso a9	ISO A9	37mm	52mm
4A <sub>16</sub>	iso a10	ISO A10	26mm	37mm

FIG.28

27/49

Value	Symbol	Meaning	Width	Height
50 <sub>16</sub>	iso b0	ISO B0	1000mm	1414mm
51 <sub>16</sub>	iso b1	ISO B1	707mm	1000mm
52 <sub>16</sub>	iso b2	ISO B2	500mm	707mm
53 <sub>16</sub>	iso b3	ISO B3	353mm	500mm
54 <sub>16</sub>	iso b4	ISO B4	250mm	353mm
55 <sub>16</sub>	iso b5	ISO B5	176mm	250mm
56 <sub>16</sub>	iso b6	ISO B6	125mm	176mm
57 <sub>16</sub>	iso b7	ISO B7	88mm	125mm
58 <sub>16</sub>	iso b8	ISO B8	62mm	88mm
59 <sub>16</sub>	iso b9	ISO B9	44mm	62mm
5A <sub>16</sub>	iso b10	ISO B10	31mm	44mm
60 <sub>16</sub>	iso c0	ISO C0	917mm	1297mm
61 <sub>16</sub>	iso c1	ISO C1	648mm	917mm
62 <sub>16</sub>	iso c2	ISO C2	458mm	648mm
63 <sub>16</sub>	iso c3	ISO C3	324mm	458mm
64 <sub>16</sub>	iso c4	ISO C4	229mm	324mm
65 <sub>16</sub>	iso c5	ISO C5	162mm	229mm
66 <sub>16</sub>	iso c6	ISO C6	114mm	162mm
67 <sub>16</sub>	iso c7	ISO C7	81mm	114mm
68 <sub>16</sub>	iso c8	ISO C8	57mm	81mm
69 <sub>16</sub>	iso designated	ISO Designated Long	110mm	220mm
70 <sub>16</sub>	iso b0	ISO B0	1030mm	1456mm
71 <sub>16</sub>	iso b1	ISO B1	728mm	1030mm
72 <sub>16</sub>	iso b2	ISO B2	515mm	728mm
73 <sub>16</sub>	iso b3	ISO B3	364mm	515mm
74 <sub>16</sub>	iso b4	ISO B4	257mm	364mm
75 <sub>16</sub>	iso b5	ISO B5	182mm	257mm
76 <sub>16</sub>	iso b6	ISO B6	128mm	182mm
77 <sub>16</sub>	iso b7	ISO B7	91mm	128mm
78 <sub>16</sub>	iso b8	ISO B8	64mm	91mm
79 <sub>16</sub>	iso b9	ISO B9	45mm	64mm
7A <sub>16</sub>	iso b10	ISO B10	32mm	45mm
80 <sub>16</sub>	index 4×6	North American Index card 4"×6"	4 inch	6 inch
81 <sub>16</sub>	index 5×8	North American Index card 5"×8"	5 inch	8 inch
90 <sub>16</sub>	Japanese_hagaki	JapaneseHagakiPostcard	100mm	148 mm
91 <sub>16</sub>	Japanese_oufuku_hagaki	JapaneseOufukuHagaki Postcard	148mm	200mm

FIG.29

address offset	msb								lsb
00 <sub>16</sub>	device dependent	economy	normal	Best	Reserved				

FIG.30

Symbol	Meaning
device_dependent	The image output will be sized as device dependent. (Mandatory)
economy	SPEED FIRST
normal	NORMAL
best	QUALITY FIRST

FIG.31

address offset	msb									lsb
00 <sub>16</sub>	device_ dependent	mono	color	Reserved						

FIG.32

Symbol	Meaning
device_dependent	The image output will be sized as device dependent. (Mandatory)
mono	MONOCHROME PRINT
color	COLOR PRINT

FIG.33

FIG. 33

address offset	msb								lsb
00 <sub>16</sub>	device_ dependent	black_ white	mono	color	Reserved				

FIG.34

Symbol	Meaning
device_dependent	The image output will be sized as device dependent.
black_white	BLACK-AND-WHITE PRINT
mono	MONOCHROME (GRAY SCALE) PRINT
color	COLOR PRINT

**FIG.35**



address offset	msb									lsb
00 <sub>16</sub>	Offset-top									
01 <sub>16</sub>										
02 <sub>16</sub>	Offset-left									
03 <sub>16</sub>										

FIG.36

Symbol	Meaning
Offset_top Offset_left	X000 <sub>16</sub> ~X999 <sub>16</sub> : OFFSET POSITION PACKED BY BCD (00.0 ~99.9mm, X=0 <sub>16</sub> : PLUS (INWARD DIRECTION OF SHEET), X=8 <sub>16</sub> : MINUS (OUTWARD DIRECTION OF SHEET)) FFFF <sub>16</sub> : device_dependent

FIG.37




FIG.38

Symbol	Meaning
Layout_type	00000000 <sub>16</sub> ~ 0FFFFFFF <sub>16</sub> : TYPE OF LAYOUT FFFFFFFF <sub>16</sub> : device_dependent

FIG.39

09/831694-07901

	msb						lsb
opcode	OPERATION MODE(41 <sub>16</sub> )						
operand [0]	subfunction						
operand [1]	status						
operand [2]	next_pic						
operand [3]	next_page						
operand [4]							
operand [5]	print_job_ID						
⋮							
operand [16]							
operand [17]	operation_mode_parameters						
⋮							
operand [24]							
operand [25]	operation_mode_optional_parameters						
⋮							
operand [29]							

FIG.40

Address Offset	Contents
00 <sub>16</sub>	media_type
01 <sub>16</sub>	media_size
02 <sub>16</sub>	print_quality
03 <sub>16</sub>	mono_color
04 <sub>16</sub>	rendering_intent

FIG.41

FIG. 41

40/49




FIG.42

41/49




FIG.43






FIG.44




FIG.45




FIG.46

1 : IT IS RAINY TODAY  
2 : IT WILL BE CLOUDY  
TOMORROW  
3 : IT WAS WARM  
YESTERDAY  
4 : XXXXXX  
5 : YYYYYY  
6 : ZZZZZZ  
7 : XXXXXX  
8 : YYYYYY  
9 : ZZZZZZ  
10 : XXXXXX  
11 : YYYYYY  
12 : ZZZZZZ





FIG.47

	msb						lsb
opcode	CAPTURE(XX <sub>16</sub> )						
opcode [0]	subfunction						
opcode [1]	source_subunit_type					source_subunit_ID	
opcode [2]	source_plug						
opcode [3]	status						
opcode [4]	reserved						
opcode [5]	print_job_ID						
⋮							
opcode [16]							
opcode [17]	data_size=00000000 <sub>16</sub>						
opcode [18]							
opcode [19]							
opcode [20]							
opcode [21]	image_size_x=0000 <sub>16</sub>						
opcode [22]							
opcode [23]	image_size_y=0000 <sub>16</sub>						
opcode [24]							
opcode [25]	image_format_specifier=0001 <sub>16</sub> (Dont Care)						
opcode [26]	Next_pic						
opcode [27]	Next_page						
opcode [28]							

FIG.48

09/831694-071901

	msb						lsb
opcode	CAPTURE(XX <sub>16</sub> )						
opcode [0]	subfunction						
opcode [1]	source_subunit_type				source_subunit_ID		
opcode [2]	source_plug						
opcode [3]	status						
opcode [4]	reserved						
opcode [5]	print_job_ID						
⋮							
opcode [16]							
opcode [17]	data_size=00000000 <sub>16</sub>						
opcode [18]							
opcode [19]							
opcode [20]							
opcode [21]	image_size_x=0000 <sub>16</sub>						
opcode [22]							
opcode [23]	image_size_y=0000 <sub>16</sub>						
opcode [24]							
opcode [25]	image_format_specifier=0000 <sub>16</sub> (sRGBraw)						
opcode [26]	Next_pic						
opcode [27]	Next_page						
opcode [28]							

FIG.49

Value	Sub-Value	Type	Meaning
<b>30<sub>16</sub></b>			<b>sRGB raw</b>
	<b>00<sub>16</sub></b>	sRGB raw	
	<b>01<sub>16</sub></b>	sRGB raw, quadlet	
<b>31<sub>16</sub></b>			<b>YCC raw</b>
	<b>0X<sub>16</sub></b>	YCC 4:2:2 raw	
	<b>1X<sub>16</sub></b>	YCC 4:2:0 raw	
	<b>X0<sub>16</sub></b>	Pixel ratio 1.00×1.00/ITU-RBT.709-2/pixel	
	<b>X1<sub>16</sub></b>	Pixel ratio 1.19×1.00/ITU-RBT.709-2/pixel	
	<b>X2<sub>16</sub></b>	Pixel ratio 0.89×1.00/ITU-RBT.709-2/pixel	
	<b>X3<sub>16</sub></b>	Pixel ratio 0.89×1.00/ITU-RBT.709-4/pixel	
	<b>X8<sub>16</sub></b>	Pixel ratio 1.00×1.00/ITU-RBT.709-2/line	
	<b>X9<sub>16</sub></b>	Pixel ratio 1.19×1.00/ITU-RBT.709-2/line	
	<b>XA<sub>16</sub></b>	Pixel ratio 0.89×1.00/ITU-RBT.709-2/line	
	<b>XB<sub>16</sub></b>	Pixel ratio 0.89×1.00/ITU-RBT.709-4/line	
<b>10<sub>16</sub></b>			<b>DCF Object</b>
	<b>00<sub>16</sub></b>	Exif2.1	
	<b>01<sub>16</sub></b>	JFIF	
	<b>02<sub>16</sub></b>	TIFF	
	<b>0F<sub>16</sub></b>	JPEG	
<b>80<sub>16</sub>~8F<sub>16</sub></b>	<b>00<sub>16</sub>~FF<sub>16</sub></b>	Vendor Dependent format	
<b>FE<sub>16</sub></b>			<b>Special meaning</b>
	<b>00<sub>16</sub></b>	Unit Plug Defined	
	<b>01<sub>16</sub></b>	Don't care	
	<b>02<sub>16</sub></b>	Null	

FIG.50

Value	Symbol	Meaning
01 <sub>16</sub>	receive	Receive the image
02 <sub>16</sub>	skip	Skin the image area
03 <sub>16</sub>	resume	Resume from the bus reset
04 <sub>16</sub>	query	Get the supported values
Other values	—	Reserved

**FIG.51**



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

# Declaration and Power of Attorney for Patent Application

## 特許出願宣言書及び委任状

### Japanese Language Declaration

#### 日本語宣言書

私は、以下に記名された発明者として、ここに下記の通り宣言する：

As a below names inventor, I hereby declare that:

私の住所、郵便の宛先そして国籍は、私の氏名の後に記載された通りである。

My residence, post office address and citizenship are as stated next to my name:

下記の名称の発明について、特許請求範囲に記載され、且つ特許が与められている発明主題に関して、私は、最初、最先且つ唯一の発明者である（唯一の氏名が記載されている場合）か、或いは最初、最先且つ共同発明者である（複数の氏名が記載されている場合）と信じている。

I believe I am the original, first and sole inventor(if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

IMAGE PRINTING SYSTEM

the specification of which is attached hereto unless the following box is checked:

上記発明の明細書はここに添付されているが、下記の欄がチェックされている場合は、この限りでない：

☒ was filed on September 11, 2000  
as United States Application Number of  
PCT International Application Number PCT/JP00/06198  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

☐ \_\_\_\_\_ の日に出願され、  
この出願の米国出願番号またはPCT国際出願番号は、  
\_\_\_\_\_ であり、且つ  
\_\_\_\_\_ の日に補正された出願（該当する場合）

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、上記の補正書によって補正された、特許請求範囲を含む上記明細書を検討し、且つ内容を理解していることをここに表明する。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

私は、連邦規則法典第37編規則1.56に定義されている、特許性について重要な情報を開示する義務があることを認める。

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the need of the individual case. Any comments on the amount of time you are required to complete this form should be sent to Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

Japanese Language Declaration

日本語宣言書

私は、ここに、以下に記載した外国での特許出願または発明者証の出願、或いは米国以外の少なくとも一国を指定している米国法典第35編第365条(a)によるPCT国際出願について、同第119条(a)(d)項又は第365条(b)項に基づいて優先権を主張するとともに、優先権を主張する本出願の出願日より前の出願日を有する外国での特許出願または発明者証の出願、或いはPCT国際出願については、いかなる出願も、下記の枠内をチェックすることにより示した。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT international application having a filing date before that of the application for which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

外国での先行出願

優先権主張なし

11-261279  
(Number)  
(番号)  
Japan  
(Country)  
(国名)

14 September 1999  
(Day/Month/Year Filed)

☐

PCT/JP00/06198  
(Number)  
(番号)  
PCT  
(Country)  
(国名)

11 September 2000  
(Day/Month/Year Filed)

☐

(Number)  
(番号)  
(Country)  
(国名)

(Day/Month/Year Filed)

☐

(Number)  
(番号)  
(Country)  
(国名)

(Day/Month/Year Filed)

☐

(Number)  
(番号)  
(Country)  
(国名)

(Day/Month/Year Filed)

☐

(Number)  
(番号)  
(Country)  
(国名)

(Day/Month/Year Filed)

☐

私は、ここに、下記のいかなる米国仮特許出願についても、その米国法典第35編第119条(e)項の利益を主張する。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)  
(出願番号)  
(Filing Date)  
(出願日)

(Application No.)  
(出願番号)  
(Filing Date)  
(出願日)

私は、ここに、下記のいかなる米国出願についても、その米国法典第35編第120条に基づく利益を主張し、又米国を指定するいかなるPCT国際出願についても、その同第365条(c)に基づく利益を主張する。また、本出願の各特許請求の範囲の主題が、米国法典第35編第112条第1段に規定された態様で、先行する米国出願又はPCT国際出願に開示されていない場合においては、その先行出願の出願日と本国内出願日またはPCT国際出願日との間の期間中に入手された情報で、連邦規則法典第37編規則1.56に定義された特許性に関わる重要な情報について開示義務があることを承認する。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Application No.)  
(出願番号)  
(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可、係属中、放棄)

私は、ここに表明された私自身の知識に係わる陳述が真実であり、且つ情報と信ずることに基づく陳述が、真実であると信じられることを宣言し、さらに、故意に虚偽の陳述などを行った場合は、米国法典第18編第1001条に基づき、罰金または拘禁、若しくはその両方により処罰され、またそのような故意による虚偽の陳述は、本出願またはそれに対して発行されるいかなる特許も、その有効性に問題が生ずることを理解した上で陳述が行われたことを、ここに宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

日本語宣言書

委任状： 私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁護士及び/または弁理士を任命する。(氏名及び登録番号を記載すること)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

WILLIAM S. FROMMER, Registration No. 25,506 and  
DENNIS M. SMID, Registration No. 34,930

Send Correspondence to:  
WILLIAM S. FROMMER, Esq.  
c/o FROMMER LAWRENCE & HAUG LLP  
745 Fifth Avenue  
New York, New York 10151

Direct Telephone Calls to:  
(212) 588-0800  
to the attention of:  
WILLIAM S. FROMMER

Full name of sole or first inventor

Yushi IHARA

inventor's signature

Date

Yushi Ihara

May 11, 2001

Residence

Kanagawa, Japan

Citizenship

Japan

Post Office Address

c/o Sony Corporation, 7-35, Kitashinagawa 6-chome,  
Shinagawa-ku, Tokyo 141-0001 Japan

full name of second joint inventor, if any

Second Inventor's signature

Date

Residence

Citizenship

Post Office Address

(Supply similar information and signature for third and subsequent joint inventors)

書類送付先

直通電話連絡先：(氏名及び電話番号)

唯一または第一発明者氏名

発明者の署名

日付

住所

国籍

郵便の宛先

第二共同発明者がいる場合、その氏名

第二共同発明者の署名

日付


住所

国籍

郵便の宛先

(第三以下の共同発明者についても同様に記載し、署名をすること)

United States Patent & Trademark Office  
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☒ Scanned copy is best available. *Drawings*